




Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



NOTE) 1 . ALL LEAD CO-PLANARITY SHALL BE 0.08mm MAX

2 CONTACT PLATING SPECIFICATIONS.

CONTACT AREA : GOLD 0.05 μ m MIN

SMT LEAD : GOLD 0.05 μ m MIN


UNDERPLATING : NICKEL 1 μ m MIN

(SURFACE : SEALING)


3 HRS MARK AND CAV NO. ARE INDICATED IN APPROX POSITION SHOWN.

4 GATE POSITION IS INDICATED IN APPROX POSITION SHOWN.

A-A (50:1)




ENGAGEMENT FIGURE (50:1)



3	PS	CLEAR (ENBOSSED CARRIER TAPE)	6	PS	CLEAR (REINFORCEMENT COLLAR)
2	PHOSPHOR BRONZE	2	5	PS	BLACK (PLASTIC REEL)
1	LCP	UL94 V-0, BLACK	4	POLYESTER	CLEAR (COVER TAPE)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 10 : 1	COUNT 	DESCRIPTION OF REVISIONS	
HIROSE ELECTRIC CO., LTD.		APPROVED : MO. ISHIDA	16. 04. 26	DRAWING NO. EDC-324406-51-00	
		CHECKED : TS. MIYAZAKI	16. 04. 26	PART NO. BM14C(0.8)-14DS-0.4V(51)	
		DESIGNED : NY. YAMASHIRO	16. 04. 26	CODE NO. CL684-8017-0-51	
		DRAWN : SN. NUMAZAKI	16. 04. 25	1/3	
		DESIGNED		CHECKED	DATE


Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

◆ RECOMMENDED PCB LAYOUT




◆ RECOMMENDED METAL MASK DIMENSIONS

METAL MASK THICKNESS : 100 μm



6 RECOMMENDED REFLOW TEMPERATURE PROFILE USING LEAD-FREE SOLDER PASTE.




- REFLOW METHOD: IR REFLOW
NUMBER OF REFLOW CYCLES: 2 CYCLES MAX.
- 1) REFLOW TIME
DURATION ABOVE 220°C, 60 SEC. MAX.
(PEAK TEMPERATURE: 250°C MAX)
 - 2) PRE-HEAT TIME
PRE-HEAT TEMPERATURE(MIN): 150°C
PRE-HEAT TEMPERATURE(MAX): 180°C
PRE-HEAT TIME: 90-120 sec.

6 THIS TEMPERATURE PROFILE IS PER THE CONDITIONS SHOWN ABOVE.
ADDITIONAL FACTORS, SUCH AS SOLDER PASTE TYPE, PCB SIZE AND
OTHER MOUNTED COMPONENTS COULD AFFECT THE PROFILE, THEREFORE,
A THOROUGH EVALUATION OF MOUNTING CONDITION IS REQUIRED
PRIOR TO PRODUCTION. TEMPERATURE IS MEASURED AT CONTACT LEAD.


HRS	DRAWING NO.	EDC-324406-51-00
	PART NO.	BM14C(0.8)-14DS-0.4V(51)
	CODE NO.	CL684-8017-0-51

Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


EMBOSSED CARRIER TAPE PACKAGING (5:1)




B-B (5:1)




C-C (5:1)



DIRECTION OF UNREELING




E(10:1)




PICK UP AREA : (0.13)

STYLE AND DIMENTION OF REEL (FREE)



D-D (FREE)



DETAIL OF PART No. LABEL

SUPPLIER
QUANTITY
PART No.
CODE No.
DATE OF MANUFACTURED


製造年月日	** ** *
製品コード	CL684-8017-0-51
製品名	BM14C<0.8>-14DS-0.4V<51>
数量	8,000
納入者	ヒロセ電機(株)

7. PER REEL 8000 CONNECTORS.

8. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

9 REFER TO JIS C 0806(PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING)

10 AFTER PACKAGING, ROLL 2 METERS OF THE REINFORCEMENT COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL POCKET, AND TAPE DOWN AT THE END THE COLLAR.



TRAILER

9 TAPING (FREE)

LEADER

HRS

DRAWING NO.	EDC-324406-51-00
PART NO.	BM14C<0.8>-14DS-0.4V<51>
CODE NO.	CL684-8017-0-51