TE Internal #: 1857724-4

Preloaded - C-Clip PCB Spring Contact, Uncompressed Height 1.8

mm [.071 in], Length 3.46 mm [.136 in], Width 1 mm [.039 in]

View on TE.com >



### Connectors > Contacts > PCB Spring Contacts











Spring Finger Type: Preloaded - C-Clip

Scalable: No

Side Protected: No

Uncompressed Height: 1.8 mm [.071 in] Product Length: 3.46 mm [.136 in]

## **Features**

## **Product Type Features**

Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Spring Finger Type	Preloaded - C-Clip
Scalable	No
Configuration Features	
Number of Positions	1
Side Protected	No

### **Contact Features**

Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Gold
Contact Base Material	Stainless Steel
Contact Working Range (Low)	1 mm[.039 in]
Contact Working Range (High)	1.6 mm[.063 in]
Point of Contact Area Plating Material	Gold
Contact Current Rating (Max)	.5 A



#### **Dimensions**

Uncompressed Height	1.8 mm[.071 in]
Product Length	3.46 mm[.136 in]
Product Width	1 mm[.039 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	6000

Tape & Reel

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts





# Customers Also Bought

















TE Part #144744-E
ERBIC BUS B BUS-SYSTEM SYS CAN
HO SC CU

## **Documents**

## **Product Drawings**

## CAD Files

Customer View Model ENG\_CVM\_CVM\_1857724-4\_G.2d\_dxf.zip

English

3D PDF

3D

Preloaded - C-Clip PCB Spring Contact, Uncompressed Height 1.8 mm [.071 in], Length 3.46 mm [.136 in], Width 1 mm [.039 in]



**Customer View Model** 

ENG\_CVM\_CVM\_1857724-4\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1857724-4\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Products for Mobile Equipment

English

**Product Specifications** 

**Product Specification** 

English