



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 150V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 500MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: Wafer LCP, UL94V-0
PIN Phosphoric bronze Tin-plated
Solder tad Phosphoric bronze Tin-plated

编 号	尺寸 (mm)	
	A	B
A1257LF-02A	1.25	7.45
A1257LF-03A	2.50	8.70
A1257LF-04A	3.75	9.95
A1257LF-05A	5.00	11.20
A1257LF-06A	6.25	12.45
A1257LF-07A	7.50	13.70
A1257LF-08A	8.75	14.95
A1257LF-09A	10.00	16.20
A1257LF-10A	11.25	17.45
A1257LF-11A	12.50	18.70
A1257LF-12A	13.75	19.95
A1257LF-30A	36.25	42.25



X. ±0.5	X* ±
.X ±0.30	X* ±
.XX ±0.20	.XX* ±
.XXX ±0.005	.XXX* ±

深圳市泰华电子有限公司

TaiHua Electronics Co., Ltd

单位 UNIT	mm	版本: VERSION	A0	产品名称 Product name	DF16带钩立贴 WAFER DIP TYPE
比例 SCALE	1:1	核准: APPROVED BY		产品编号 Product No.	TH-A1257LF-VA
		审核: CHECKED BY		制图: DRAWN BY	
		封文: DATE	2022.9.2	客户编号 Client No.	