

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 32 A, number of connections: 3, connection method: Spring-cage connection, 1 level, Rated cross section: 4 mm<sup>2</sup>, cross section: 0.08 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: red

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 3037520                        |
| Packing unit                         | 50 pc                          |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | BE2112                         |
| Catalog page                         | Page 141 (CL-2009)             |
| GTIN                                 | 4017918812416                  |
| Weight per piece (including packing) | 12.2 g                         |
| Weight per piece (excluding packing) | 10.904 g                       |
| Country of origin                    | DE                             |

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## Technical data

### Product properties

|                       |                                |
|-----------------------|--------------------------------|
| Product type          | Multi-conductor terminal block |
| Number of connections | 3                              |
| Number of rows        | 1                              |
| Potentials            | 1                              |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
|----------------------|-----|

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 1.02 W |

### Connection data

|                                 |                   |
|---------------------------------|-------------------|
| Number of connections per level | 3                 |
| Nominal cross section           | 4 mm <sup>2</sup> |

#### 1 level

|                                                                   |                                                                                                                                                                   |
|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Stripping length                                                  | 10 mm                                                                                                                                                             |
| Internal cylindrical gage                                         | A4                                                                                                                                                                |
| Connection in acc. with standard                                  | IEC 60947-7-1                                                                                                                                                     |
| Conductor cross section rigid                                     | 0.08 mm <sup>2</sup> ... 6 mm <sup>2</sup>                                                                                                                        |
| Cross section AWG                                                 | 28 ... 10 (converted acc. to IEC)                                                                                                                                 |
| Conductor cross section flexible                                  | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                        |
| Conductor cross section, flexible [AWG]                           | 28 ... 12 (converted acc. to IEC)                                                                                                                                 |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                        |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                        |
| Nominal current                                                   | 32 A (with 6 mm <sup>2</sup> conductor cross section)                                                                                                             |
| Maximum load current                                              | 38 A (In the case of a 6 mm <sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors) |
| Nominal voltage                                                   | 800 V                                                                                                                                                             |
| Nominal cross section                                             | 4 mm <sup>2</sup>                                                                                                                                                 |

### Ex data

#### Rated data (ATEX/IECEx)

|                             |                                                                                      |
|-----------------------------|--------------------------------------------------------------------------------------|
| Identification              | Ex II 2 G Ex eb IIC Gb                                                               |
| Operating temperature range | -60 °C ... 110 °C                                                                    |
| Ex-certified accessories    | 3031704 D-ST5 4<br>3024481 ATP-ST 6<br>1204517 SZF 1-0,6X3,5<br>3022276 CLIPFIX 35-5 |

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

|                                                    |                                     |
|----------------------------------------------------|-------------------------------------|
|                                                    | 3022218 CLIPFIX 35                  |
| List of bridges                                    | Plug-in bridge / FBS 2-6 / 3030336  |
|                                                    | Plug-in bridge / FBS 3-6 / 3030242  |
|                                                    | Plug-in bridge / FBS 4-6 / 3030255  |
|                                                    | Plug-in bridge / FBS 5-6 / 3030349  |
|                                                    | Plug-in bridge / FBS 10-6 / 3030271 |
|                                                    | Plug-in bridge / FBS 20-6 / 3030365 |
|                                                    | Plug-in bridge / FBS 50-6 / 3032224 |
| Bridge data                                        | 27 A / 4 mm <sup>2</sup>            |
| Ex temperature increase                            | 40 K (30 A / 4 mm <sup>2</sup> )    |
| Rated voltage                                      | 550 V                               |
| for bridging with bridge                           | 550 V                               |
| - At bridging between non-adjacent terminal blocks | 352 V                               |
| - At cut-to-length bridging                        | 352 V                               |
| - At cut-to-length bridging with cover             | 352 V                               |
| - At cut-to-length bridging with partition plate   | 550 V                               |
| Rated insulation voltage                           | 500 V                               |
| output                                             | (Permanent)                         |

## Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 30 A    |
| Maximum load current | 33 A    |
| Contact resistance   | 0.75 mΩ |

## Ex connection data General

|                              |                                            |
|------------------------------|--------------------------------------------|
| Nominal cross section        | 4 mm <sup>2</sup>                          |
| Rated cross section AWG      | 12                                         |
| Connection capacity rigid    | 0.08 mm <sup>2</sup> ... 6 mm <sup>2</sup> |
| Connection capacity AWG      | 28 ... 10                                  |
| Connection capacity flexible | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Connection capacity AWG      | 28 ... 12                                  |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 6.2 mm  |
| End cover width    | 2.2 mm  |
| Height             | 64.5 mm |
| Depth on NS 35/7,5 | 43 mm   |
| Depth on NS 35/15  | 50.5 mm |

## Material specifications

|                                        |     |
|----------------------------------------|-----|
| Color                                  | red |
| Flammability rating according to UL 94 | V0  |
| Insulating material group              | I   |
| Insulating material                    | PA  |

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)                                                     |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C ( )                                                                                                          |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## Drawings

Circuit diagram



# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3037520>

| CSA<br>Approval ID: 13631 |                       |                       |                   |                             |
|---------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B               | 600 V                 | 30 A                  | 28 - 10           | -                           |
| Use group C               | 600 V                 | 30 A                  | 28 - 10           | -                           |

| CCA<br>Approval ID: CH-02-IK-0258.I |                       |                       |                   |                             |
|-------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                     | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                     | -                     | -                     | -                 | - 1.5                       |

| cULus Recognized<br>Approval ID: E60425 |                       |                       |                   |                             |
|-----------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                             | 600 V                 | 30 A                  | 28 - 10           | -                           |
| Use group C                             | 600 V                 | 30 A                  | 28 - 10           | -                           |

| DNV<br>Approval ID: TAE00001CS |  |  |  |  |
|--------------------------------|--|--|--|--|
|--------------------------------|--|--|--|--|

| EAC Ex<br>Approval ID: RU C-DE.HA91.B.00066 |  |  |  |  |
|---------------------------------------------|--|--|--|--|
|---------------------------------------------|--|--|--|--|

| IECEx<br>Approval ID: IECExPTB07.0024U |  |  |  |  |
|----------------------------------------|--|--|--|--|
|----------------------------------------|--|--|--|--|

| ATEX<br>Approval ID: PTB07ATEX1027U |  |  |  |  |
|-------------------------------------|--|--|--|--|
|-------------------------------------|--|--|--|--|

| CCC<br>Approval ID: 2020322313000621 |  |  |  |  |
|--------------------------------------|--|--|--|--|
|--------------------------------------|--|--|--|--|

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



**UKCA-EX**

Approval ID: CSAE 22UKEX1141U

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## Accessories

**i** Note: Applying some accessories below might limit this product.

### FBS 2-6 - Plug-in bridge

3030336

<https://www.phoenixcontact.com/us/products/3030336>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

**i** Max. current carrying capacity: 32 A

### FBS 3-6 - Plug-in bridge

3030242

<https://www.phoenixcontact.com/us/products/3030242>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red

**i** Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## FBS 4-6 - Plug-in bridge

3030255

<https://www.phoenixcontact.com/us/products/3030255>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 32 A

---

## FBS 5-6 - Plug-in bridge

3030349

<https://www.phoenixcontact.com/us/products/3030349>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

 Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## FBS 6-6 - Plug-in bridge

1008238

<https://www.phoenixcontact.com/us/products/1008238>



Plug-in bridge, One side not fully isolated, pitch: 6.2 mm, number of positions: 6, color: red

---

## FBS 10-6 - Plug-in bridge

3030271

<https://www.phoenixcontact.com/us/products/3030271>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

 Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## FBS 20-6 - Plug-in bridge

3030365

<https://www.phoenixcontact.com/us/products/3030365>



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: red

 Max. current carrying capacity: 32 A

---

## FBSR 2-6 - Plug-in bridge

3033715

<https://www.phoenixcontact.com/us/products/3033715>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 24 A

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## FBSR 3-6 - Plug-in bridge

3001594

<https://www.phoenixcontact.com/us/products/3001594>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red

 Max. current carrying capacity: 24 A

---

## FBSR 4-6 - Plug-in bridge

3001595

<https://www.phoenixcontact.com/us/products/3001595>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 24 A

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## FBSR 5-6 - Plug-in bridge

3001596

<https://www.phoenixcontact.com/us/products/3001596>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

 Max. current carrying capacity: 24 A

---

## FBSR 10-6 - Plug-in bridge

3033716

<https://www.phoenixcontact.com/us/products/3033716>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

 Max. current carrying capacity: 24 A

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## FBSRH 2-6 - Short-circuit connector

3033812

<https://www.phoenixcontact.com/us/products/3033812>



Short-circuit connector, pitch: 6.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 24 A

---

## FBS 2-6 BU - Plug-in bridge

3036932

<https://www.phoenixcontact.com/us/products/3036932>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: blue

 Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## FBS 3-6 BU - Plug-in bridge

3036945

<https://www.phoenixcontact.com/us/products/3036945>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: blue

 Max. current carrying capacity: 32 A

---

## FBS 4-6 BU - Plug-in bridge

3036958

<https://www.phoenixcontact.com/us/products/3036958>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: blue

 Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## FBS 5-6 BU - Plug-in bridge

3036961

<https://www.phoenixcontact.com/us/products/3036961>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: blue

 Max. current carrying capacity: 32 A

---

## FBS 10-6 BU - Plug-in bridge

3032198

<https://www.phoenixcontact.com/us/products/3032198>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: blue

 Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block

3037520


<https://www.phoenixcontact.com/us/products/3037520>



## FBS 20-6 BU - Plug-in bridge

3032208

<https://www.phoenixcontact.com/us/products/3032208>



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: blue

 Max. current carrying capacity: 32 A

---

## FBS 50-6 BU - Plug-in bridge

3032211

<https://www.phoenixcontact.com/us/products/3032211>



Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: blue

 Max. current carrying capacity: 32 A

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## D-STTS 4 - End cover

3031704

<https://www.phoenixcontact.com/us/products/3031704>

End cover, depth: 43 mm, width: 2.2 mm, height: 64.5 mm, color: gray



---

## ATP-ST 6 - Partition plate

3024481

<https://www.phoenixcontact.com/us/products/3024481>

Partition plate, depth: 47.2 mm, width: 2 mm, height: 73.5 mm, color: gray



# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## WST 4 - Warning cover

3030954

<https://www.phoenixcontact.com/us/products/3030954>



Warning cover, Strip, yellow, labeled, mounting type: plug in, for terminal block width: 6.2 mm, lettering field size: 4.5 x 5.55 mm, Number of individual labels: 5

---

## D-STX 4 OG - End cover

3037591

<https://www.phoenixcontact.com/us/products/3037591>

End cover, width: 2.2 mm, height: 43 mm, color: orange



# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## LPS-6/E - Service connector

3270540

<https://www.phoenixcontact.com/us/products/3270540>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

---

## LPS-6 - Service connector

3270541

<https://www.phoenixcontact.com/us/products/3270541>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## LPO 4/E - Pick-off plug

3270519

<https://www.phoenixcontact.com/us/products/3270519>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

---

## LPO 4 - Pick-off plug

3270522

<https://www.phoenixcontact.com/us/products/3270522>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/us/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/us/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/us/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/us/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/us/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/us/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/us/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/us/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/us/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



---

## ISH 4/0,5 - Insulating sleeve

3002885

<https://www.phoenixcontact.com/us/products/3002885>

Insulating sleeve, color: gray



# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## ISH 4/1,0 - Insulating sleeve

3002898

<https://www.phoenixcontact.com/us/products/3002898>



Insulating sleeve, color: black

---

## PAI-4-FIX-5/6 BU - Test adapter

3035975

<https://www.phoenixcontact.com/us/products/3035975>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## PAI-4-FIX-5/6 OG - Test adapter

3035974

<https://www.phoenixcontact.com/us/products/3035974>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 YE - Test adapter

3035977

<https://www.phoenixcontact.com/us/products/3035977>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## PAI-4-FIX-5/6 RD - Test adapter

3035976

<https://www.phoenixcontact.com/us/products/3035976>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 GN - Test adapter

3035978

<https://www.phoenixcontact.com/us/products/3035978>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## PAI-4-FIX-5/6 BK - Test adapter

3035980

<https://www.phoenixcontact.com/us/products/3035980>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 GY - Test adapter

3035982

<https://www.phoenixcontact.com/us/products/3035982>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## PAI-4-FIX-5/6 VT - Test adapter

3035979

<https://www.phoenixcontact.com/us/products/3035979>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 BN - Test adapter

3035981

<https://www.phoenixcontact.com/us/products/3035981>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## PAI-4-FIX-5/6 WH - Test adapter

3035983

<https://www.phoenixcontact.com/us/products/3035983>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PS-6 - Test plug

3030996

<https://www.phoenixcontact.com/us/products/3030996>



Test plug, Modular test plug, number of positions: 1, color: red

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## PS-6/2,3MM RD - Test plug

3038736

<https://www.phoenixcontact.com/us/products/3038736>

Test plug, number of positions: 1, color: red



---

## E/AL-NS 35 - End bracket

1201662

<https://www.phoenixcontact.com/us/products/1201662>

End clamp, for end support of UKH 50 to UKH 240, is pushed onto DIN rail NS 35 and fixed with 2 screws, width: 10 mm, color: aluminum



# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## ZB 6:UNBEDRUCKT - Zack marker strip

1051003

<https://www.phoenixcontact.com/us/products/1051003>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

---

## ZB 6 CUS - Zack marker strip

0824992

<https://www.phoenixcontact.com/us/products/0824992>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

<https://www.phoenixcontact.com/us/products/1051016>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15 x 10.5 mm, Number of individual labels: 10

---

## ZB 6,QR:FORTL.ZAHLEN - Zack marker strip

1051029

<https://www.phoenixcontact.com/us/products/1051029>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15 x 10.5 mm, Number of individual labels: 10

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## ZB 6,LGS:GLEICHE ZAHLEN - Zack marker strip

1051032

<https://www.phoenixcontact.com/us/products/1051032>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

---

## ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414

<https://www.phoenixcontact.com/us/products/1051414>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## ZB 6,LGS:U-N - Marker for terminal blocks

1051430

<https://www.phoenixcontact.com/us/products/1051430>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

---

## UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/us/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

# STS 4-TWIN RD - Feed-through terminal block



3037520

<https://www.phoenixcontact.com/us/products/3037520>

## UC-TM 6 CUS - Marker for terminal blocks

0824589

<https://www.phoenixcontact.com/us/products/0824589>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

---

## UCT-TM 6 - Marker for terminal blocks

0828736

<https://www.phoenixcontact.com/us/products/0828736>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## UCT-TM 6 CUS - Marker for terminal blocks

0829602

<https://www.phoenixcontact.com/us/products/0829602>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

---

## SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/us/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

# STS 4-TWIN RD - Feed-through terminal block

3037520

<https://www.phoenixcontact.com/us/products/3037520>



## ST-BW - Actuation tool

1207608

<https://www.phoenixcontact.com/us/products/1207608>

Actuation tool, for all 2.5 mm<sup>2</sup> - 4.0 mm<sup>2</sup> spring-cages



---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)