

## Printed-circuit board connector - MSTBT 2,5/ 2-STF-5,08 BD:+,- - 1715214

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 2, Pitch: 5.08 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin



The figure shows a 10-position version of the product



### Key Commercial Data

Packing unit	1
GTIN	 4 055626 389738
GTIN	4055626389738
Custom tariff number	85366990

### Technical data

#### Dimensions

Length	18.2 mm
Height	15 mm
Width	19.96 mm
Pitch	5.08 mm
Dimension a	5.08 mm

#### General

Number of positions	2
Connection method	Screw connection with tension sleeve
Insulating material group	I
Rated voltage (III/2)	320 V
Nominal current I <sub>N</sub>	12 A

## Printed-circuit board connector - MSTBT 2,5/ 2-STF-5,08 BD:+,- - 1715214

### Technical data

#### General

Flammability rating according to UL 94	V0
Screw thread	M3

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

#### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"