

Product: 9451WB ☑



Audio Cable, 1 Pair 22 AWG, TC, Shielded, Waterblocked

# **Product Description**

Audio Cable, 1 Pair 22 AWG stranded (7x30) TC conductors, polypropylene insulation, overall Beldfoil® shield (100% coverage), 22 AWG stranded TC drain wire, waterblock tape, polyethylene jacket.

## **Technical Specifications**

### **Product Overview**

Suitable Applications:	Automatic Stripping Equipment; Low Voltage analog Signals (4-20mA, 0-10V,); Low Voltage Digital Control (24V,); Line Level audio; Computer Communication; Panel Wiring
------------------------	--

#### **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	22 AWG	7x30	TC - Tinned Copper

## Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PP - Polypropylene	0.0085 in (0.22 mm)	0.046 in (1.2 mm)	Black & Red

## Outer Shield

Tano Ri Laminato (Alum+Poly) 100% 22 AWG (7x30) TC	Shield Type	Material	Coverage	Drainwire Type
Tape Di-Laminate (Alumiri Oly) 100% 22 AWG (7330) TO	Таре	Bi-Laminate (Alum+Poly)	100%	22 AWG (7x30) TC

Table Notes:

Outer Shield Waterblocking Tape

### Outer Jacket

Material	Nom. Thickne	ss	Nom. Diameter
PE - Polyethylene	0.020 in (0.51 mm)		0.165 in
Overall Cable Dian (Nominal):	neter	0.16	35 in

## **Electrical Characteristics**

### Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Velocity of Prop.	Max. Current
18.2 Ohm/1000ft	35 pF/ft (110 pF/m)	67 pF/ft (220 pF/m)	66%	6 Amps per Conductor at 30°C

## Voltage

UL Voltage Rating 300 V

### **Mechanical Characteristics**

### Temperature

UL Temperature	Operating
60°C	-20°C to +60°C

#### **Bend Radius**

Stationary Min.	Installation Min.
1.65 in (41.9 mm)	1.65 in

Max. Pull Tension:	27 lbs (12 kg)
Bulk Cable Weight:	11 lbs/1000ft

## **Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### **Product Notes**

Notes:	The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

## **History**

Update and Revision:	Revision Number: 0.366 Revision Date: 02-15-2024

#### **Part Numbers**

## Variants

ltem #	Color	Putup Type	Length	UPC
9451WB 010U1000	Black	UnReel	1,000 ft	612825253198

### © 2024 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.