1-1670214-1 ACTIVE

AMP | Heavy Duty Sealed Connector Series

TE Internal #: 1-1670214-1

Housing for Male Terminals, Wire-to-Wire, 7 Position, 4 mm / 6 mm [.157 in / .236 in] Centerline, Sealable, Black, Heavy Duty Sealed

Connector Series

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Heavy Duty Sealed Connector Series Housings



Connector System: Wire-to-Wire

Number of Positions: 7

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 4 mm, 6 mm [.157 in, .236 in]

Sealable: Yes

All Heavy Duty Sealed Connector Series Housings (204)

Features

Product Type Features

Mixed & Hybrid Connector Connector Shape Rectangular Connector System Wire-to-Wire Connector & Housing Type Housing for Male Terminals Sealable Yes Connector & Contact Terminates To Wire & Cable Primary Locking Feature On the Terminal Configuration Features Number of Positions 7 Number of Rows 2 Electrical Characteristics Operating Voltage 60 VDC	Troduct Type readures	
Connector System Connector & Housing Type Housing for Male Terminals Sealable Yes Connector & Contact Terminates To Wire & Cable Primary Locking Feature On the Terminal Configuration Features Number of Positions Number of Rows 2 Electrical Characteristics	Mixed & Hybrid Connector	Yes
Connector & Housing Type Sealable Yes Connector & Contact Terminates To Wire & Cable Primary Locking Feature On the Terminal Configuration Features Number of Positions 7 Number of Rows 2 Electrical Characteristics	Connector Shape	Rectangular
Sealable Connector & Contact Terminates To Wire & Cable Primary Locking Feature On the Terminal Configuration Features Number of Positions 7 Number of Rows 2 Electrical Characteristics	Connector System	Wire-to-Wire
Connector & Contact Terminates To Primary Locking Feature On the Terminal Configuration Features Number of Positions 7 Number of Rows 2 Electrical Characteristics	Connector & Housing Type	Housing for Male Terminals
Primary Locking Feature Configuration Features Number of Positions 7 Number of Rows 2 Electrical Characteristics	Sealable	Yes
Configuration Features Number of Positions 7 Number of Rows 2 Electrical Characteristics	Connector & Contact Terminates To	Wire & Cable
Number of Positions 7 Number of Rows 2 Electrical Characteristics		
Number of Rows 2 Electrical Characteristics	Primary Locking Feature	On the Terminal
Electrical Characteristics		On the Terminal
	Configuration Features	
Operating Voltage 60 VDC	Configuration Features Number of Positions	7
	Configuration Features Number of Positions Number of Rows	7

180°, 90°

Black

А

Body Features

Cable Exit Angle

Primary Product Color

Connector & Keying Code



Contact Features

Contact Size	1.6mm, 2.8mm
Contact Type	Tab
Mating Tab Width	1.6 mm, 2.8 mm[.063 in][.11 in]
Contact Current Rating (Max)	40 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF30
Centerline (Pitch)	4 mm, 6 mm[.157 in][.236 in]

Dimensions

Connector Height	39.8 mm[1.567 in]
Product Width	48.1 mm[1.894 in]
Product Length	42.5 mm[1.673 in]
Row-to-Row Spacing	5.6 mm, 6.5 mm[.22 in][.256 in]

Usage Conditions

Operating Temperature (Max)	140 °C[284 °F]
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]

Operation/Application

Circuit Application	Power	
---------------------	-------	--

Industry Standards

Degree of Protection	IP67
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	250
Packaging Method	Box

Other



Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-H3399-B128 Heavy Duty Sealed Connector Series Backshells









TE Part # 828905-1 SINGLE-WIRE-SEAL(5MM HOLE)



TE Part # 2112293-1 PROTECTION CAP, GROUP C, ASSY



TIMER, RECEPTACLE AND TAB





Also in the Series | Heavy Duty Sealed Connector Series











Data Connectivity Housings(16)



Other Automotive Connector Accessories(34)



PCB Headers & Receptacles(1)

Customers Also Bought





TE Part #1670364-1 COVER,180 GROUP C




TE Part #1-1418480-1 7 POS MIXED REC HSG CODA

















Documents

Product Drawings

7POS, MIXED, TAB HSG, ASSY, CODA

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1670214-1_J.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1670214-1_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1670214-1_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

HDSCS Catalog

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Housing for Male Terminals, Wire-to-Wire, 7 Position, 4 mm / 6 mm [.157 in / .236 in] Centerline, Sealable, Black, Heavy Duty Sealed Connector Series



Application Specification

English