

Available SmartSlot™ Interface Quantity	1
Pre-Installed SmartSlot™ Cards	<a href="#">AP9619</a>
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Physical

Maximum Height	572.00 mm
Maximum Width	472.00 mm
Maximum depth	688.00 mm
Rack Height	13U
Net Weight	134.09 KG
Shipping Weight	166.36 KG
Shipping Height	787.00 mm
Shipping Width	599.00 mm
Shipping Depth	997.00 mm
Color	Black,Silver
Units per Pallet	1.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-4500 meters
Audible noise at 1 meter from surface of unit	62.00 dBA
Online Thermal Dissipation	2762.00 BTU/hr

Conformance

Regulatory Approvals	C-tick,CE,EN 50091 -1,EN 50091-2,EN 55022 Class A,EN 55024,EN 60950,60950,VDE
Standard Warranty	2 years repair or replace

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the