




MTA 156

TE Internal #: 644752-9

PCB Mount Header, Vertical, Wire-to-Board, 9 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Power, MTA 156

[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

Connector System: **Wire-to-Board**

Number of Positions: **9**

Number of Rows: **1**

Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Power Positions	9
Number of Columns	9
Number of Loaded Positions	9
Connector Contact Load Condition	Fully Loaded
Number of Positions	9
Number of Rows	1

PCB Mount Orientation	Vertical
-----------------------	----------

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Mating Area Length	10.16 mm[.4 in]
Contact Size	1.14mm
Mating Square Post Dimension	1.14 mm[.045 in]
PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]
Contact Layout	Inline
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
Contact Shape & Form	Square
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Tin
Contact Type	Tab
Contact Current Rating (Max)	14.24 A

Termination Features

Square Termination Post & Tail Dimension	1.14 mm[.045 in]
Termination Post & Tail Length	4.45 mm[.175 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Retention	With
Panel Mount Feature	Without
Mating Retention Type	Friction Lock
Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	Without
PCB Mount Retention	Without



Housing Features

Mating Entry Location	Top
Housing Material	Thermoplastic Polyester - Glass-Filled
Centerline (Pitch)	3.96 mm[.156 in]

Dimensions

Connector Length	35.66 mm[1.404 in]
Connector Height	10.79 mm[.425 in]
Connector Width	7.62 mm[.3 in]
PCB Thickness (Recommended)	2.36 – 3.18 mm[.093 – .125 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

UL Rating	Recognized
Glow Wire Rating	Standard Part - Not Glow Wire
Compatible With Agency/Standards Products	CSA, UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	1000
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC



Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-103156-WBHSM Receptacle Housing: Wire-to-Board, with Mating Alignment, SL156	TE Part # 640251-9 09P SL156 HSG W/O LCK RAMP	TE Part # 3-643817-9 09P MTA156 CONN ASSY 18AWG LF	TE Part # 3-643818-9 09P MTA156 CONN ASSY 20AWG YEL
TE Part # 3-640426-9 09P MTA156 CONN ASSY 18AWG ORA	TE Part # 3-640428-9 09P MTA156 CONN ASSY 22AWG RED	TE Part # 3-640599-9 09P MTA156 CONN ASSY 18AWG ORA	TE Part # 3-640427-9 09P MTA156 CONN ASSY 20AWG YEL
TE Part # 3-643819-9 09P MTA156 CONN ASSY 22AWG RED	TE Part # 3-640429-9 09P MTA156 CONN ASSY 24AWG WHT	TE Part # 640551-9 09P MTA156 COVER	TE Part # 643067-9 09P MTA156 MOLDED COVER



TE Part # 643071-9
09P MTA156 FD-THRU COVER

TE Part # 3-640432-9
09P MTA156 CONN ASSY 20AWG YEL

TE Part # 3-640433-9
09P MTA156 CONN ASSY 22AWG RED

TE Part # 640643-9
09P MTA156 COVER F/T

TE Part # 3-640431-9
09P MTA156 CONN ASSY 18AWG ORA

TE Part # 3-643820-9
09P MTA156 CONN ASSY 24AWG LF

TE Part # 3-640600-9
09P MTA156 CONN ASSY 20AWG LF

TE Part # 3-644465-9
09P MTA156 CONN ASSY 18AWG ORA

Also in the Series | MTA 156

Connector Caps & Covers(89)

Connector Contacts(4)

Connector Hardware(2)

Insertion & Extraction Tools(1)

PCB Headers & Receptacles(677)

Rectangular Power Connectors(331)

Standard Rectangular Connectors(336)

Customers Also Bought

TE Part #5650860-5
ASSEMBLY,RECEPTACLE,EUROCARD, T

TE Part #8-87589-5
08 MODII HDR DRST SHRD .100CL

TE Part #1-644752-2
12P MTA156 HDR ASSY SQ STR F/L

TE Part #644752-8
08P MTA156 HDR ASSY SQ STR F/L



TE Part #640467-1
05P UMNL HDR ASSY

TE Part #2176404-6
3550 22K 1%

TE Part #2-2176405-4
3550 22K 5%

TE Part #350765-5
15P UMNL HDR ASSY PC LF

TE Part #1622363-5
LR1 1% 1K78

Documents

Product Drawings

09P MTA156 HDR ASSY SQ STR F/L

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_644752-9_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_644752-9_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_644752-9_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL

English

UL

English

644752-9

PCB Mount Header, Vertical, Wire-to-Board, 9 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Power, MTA 156

