

1424836

https://www.phoenixcontact.com/us/products/1424836

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B32, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M32, height: 94 mm, cable gland: none, Standard

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial data

Item number	1424836
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 644 (C-2-2019)
GTIN	4055626382418
Weight per piece (including packing)	439.6 g
Weight per piece (excluding packing)	425.6 g
Customs tariff number	85389099
Country of origin	CN



1424836

https://www.phoenixcontact.com/us/products/1424836

Technical data

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Туре	B32
No. of cable outlets	1
Type of the screw connection	1x M32
Туре	Tall design
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	3. 94 . 62,5
Width	82.5 mm
Height	94 mm
Length	94 mm

Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated

Mechanical properties

Mechanical data

Type of the screw connection	1x M32
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C





1424836

https://www.phoenixcontact.com/us/products/1424836

Drawings

Dimensional drawing





Dimensional drawing



1424836

https://www.phoenixcontact.com/us/products/1424836

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1424836

DNV

Approval ID: TAE000037S



cUL RecognizedApproval ID: E255026



UL RecognizedApproval ID: E255026



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized



1424836

https://www.phoenixcontact.com/us/products/1424836

Classifications

ECLASS

	ECLASS-11.0	27440202
	ECLASS-12.0	27440202
	ECLASS-13.0	27440202
ETIM		
	ETIM 9.0	EC000437
UNSPSC		
	UNSPSC 21.0	31261500



1424836

https://www.phoenixcontact.com/us/products/1424836

Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1424836

https://www.phoenixcontact.com/us/products/1424836

Accessories

HC-B32-HCWD-PLR-BK - Protective cover

1346555

https://www.phoenixcontact.com/us/products/1346555




Protective cover B32, with double locking latch, protective cover material: PC, height: 26.4 mm, seal: yes

US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085







1424836

https://www.phoenixcontact.com/us/products/1424836

US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 M32 BK - Screw connection

3240900

https://www.phoenixcontact.com/us/products/3240900



Cable gland, metric thread, IP66 protection, straight



1424836

https://www.phoenixcontact.com/us/products/1424836

WP-G HF IP69K M32 BK - Screw connection

3240886

https://www.phoenixcontact.com/us/products/3240886



Cable gland, metric thread, IP68/69k protection, straight

WP-GA HF IP66 M32 BK - Screw connection

3240928

https://www.phoenixcontact.com/us/products/3240928

Cable gland, metric thread, IP66 protection, angled





1424836

https://www.phoenixcontact.com/us/products/1424836

WP-GA HF IP69K M32 BK - Screw connection

3240914

https://www.phoenixcontact.com/us/products/3240914

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M32 BK - Screw connection

3240956

https://www.phoenixcontact.com/us/products/3240956

Cable gland, metric thread, IP66 protection, with strain relief





1424836

https://www.phoenixcontact.com/us/products/1424836

WP-GR HF IP69K M32 BK - Screw connection

3240942

https://www.phoenixcontact.com/us/products/3240942



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M32 - Screw connection

3241000

https://www.phoenixcontact.com/us/products/3241000

Cable gland made from PP with metric thread, IP65 protection



1424836

https://www.phoenixcontact.com/us/products/1424836

WP-GT PP HF M32 - Screw connection

3241014

https://www.phoenixcontact.com/us/products/3241014



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M32 - Screw connection

3241049

https://www.phoenixcontact.com/us/products/3241049



Cable gland made from brass with metric thread, IP40 protection



1424836

https://www.phoenixcontact.com/us/products/1424836

WP-GT BRASS M32 - Screw connection

3241035

https://www.phoenixcontact.com/us/products/3241035



Cable gland made from brass with metric thread, rotatable, IP40 protection

WP-G BRASS IP65 M32 - Screw connection

3241063

https://www.phoenixcontact.com/us/products/3241063



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com