

IMPEDANCE MATCHING PAD, N

6001.00.0001

Properties

- Low insertion loss
- High repeatability
- Low return loss



Material data

Interface side 1	N / plug (male)
Standard side 1	IEC 60169-16_MIL-STD-348A/304_CEECC 22210
Center contact, material / plating	Brass / Gold Plating (Nickel underplated)
Outer contact, material / plating	Brass / SUCOPLATE (R) Plating
Body, material / plating	Brass / SUCOPLATE (R) Plating
Insulator, material	PFA / PTFE
Coupling nut, material / plating	Brass / SUCOPLATE (R) Plating
Gasket material	VMQ (Silicone rubber)
Interface side 2	BNC / jack (female)
Standard side 2	IEC 60169-8_MIL-STD-348A/301_CEECC 22120
Outer contact, material / plating	Brass / SUCOPLATE (R) Plating
Body, material / plating	Brass / SUCOPLATE (R) Plating
Insulator, material	PFA / PTFE

Electrical data

Impedance nominal	50 Ω (side 1) / 75 Ω (side 2)
Frequency frame	0 GHz to 1 GHz
Attenuation nominal	5.7 dB
Voltage division	50 Ω to 75 Ω 4 dB / 75 Ω to 50 Ω 7.5 dB

Electrical bands

	Band 1	Band 2
Frequency range	0 GHz ... 0.5 GHz	0.5 GHz ... 1 GHz
VSWR max side 1	1.15	1.25
VSWR max side 2	1.15	1.25

IMPEDANCE MATCHING PAD, N
6001.00.0001

Electrical remarks	
Power rating	0.7 W at 40 °C ambient temperature. Linearly derated to 0 W at 125 °C ambient temperature.
Electrical remarks	The power attenuation is 5.7 dB in both directions.
Mechanical data	
Weight	0.045 kg
Ordering Information Table	
Item number	Item description
22649583	6001.00.0001

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1819 / Date of publication: 07.11.2023 / uncontrolled copy