



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **80**

Number of Rows: **2**

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Stacking Configuration	Stack Through
Number of Columns	40
Number of Loaded Positions	80
Stackable	Yes
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	80



Number of Rows	2
Board-to-Board Configuration	Parallel

Body Features

Connector Profile	Low
Primary Product Color	Black

Contact Features

PCB Contact Termination Area Plating Material Thickness	4 – 6 µm[157.48 – 236.22 µin]
Contact Layout	Matrix
Contact Shape & Form	Dual Beam
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Socket
Contact Current Rating (Max)	1 A

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

Mounting Alignment Feature Length	.75 mm[.029 in]
PCB Mount Alignment Type	Locating Posts
PCB Mount Retention Type	Location Peg
Mating Alignment	With
Mating Alignment Type	Polarization
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	1.27 mm[.05 in]
Housing Material	LCP

Dimensions

Connector Length	55.88 mm[2.2 in]
Connector Height	6.25 mm[.246 in]



Connector Width	7 mm[.276 in]
Profile Height from PCB	6.25 mm[.246 in]
Row-to-Row Spacing	1.27 mm[.05 in]
Stack Height	6.25 mm[.246 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Shielded	No
Circuit Application	Power & Signal

Industry Standards

Compatible With Agency/Standards Products	DIN, UL
Compatible With Approved Standards Products	UL
Industry Standard	IEC
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Reel Diameter	330 mm[12.99 in]
Packaging Quantity	280
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-0A3-D127
Board-to-Board Adapter, Vertical, Cable Mount

TE Part # 154767-E
SMCB 80 M AB VV 7-03 CL * 0007 137 E004

TE Part # 234210-E
SMCQ 80 M AB VV 8-23 CL * H007 137 E005

TE Part # 244840-E
SMCQ 80 M AB VV 8-13 CL * H007 137 E005

TE Part # 244858-E
SMCQ 80 M AB VV 8-03 CL * H007 137 E005

TE Part # 144185-E
SMCQ 80 M AB VV 3-04 * 2,8 0003 137 E001

Also in the Series | ERNI SMC

Board-In Connectors(6)

Connector Adapters & Connector Savers(45)

PCB Headers & Receptacles(81)

Pluggable I/O Cable Assemblies(27)




Wire-to-Board Connector Assemblies
& Housings(5)

Customers Also Bought



TE Part #1-1879417-0
CPF 0603 430K 0.1% 25PPM 1K RL



TE Part #154718-E
SMCB 26 F AB VV 7-03 CL * H007 137 E002



TE Part #244837-E
SMCQ 26 M AB VV 8-13 CL * H007 137 E005



TE Part #2102444-1
FORTIS LRM,RIGHT ANGLE MODULE, UPM



TE Part #2226784-1
FORTIS LRM, BACKPLANE, 3 BAY SHELL




TE Part #154767-E
SMCB 80 M AB VV 7-03 CL * 0007 137 E004




TE Part #2102449-1
FORTIS LRM, BLANK RIGHT ANGLE HEADER



TE Part #384471-E
SRCA 2,54 4 M 1 SMD 137 E1 094 * GURT *



TE Part #AGC052N00001100000
623 receptacle angled rotatable



TE Part #AKA020N00390113000
623 extension, speedtec

Documents

Product Drawings

SMCB 80 F AB VV 7-13 CL * H007 137 E002

English

CAD Files

Customer View Model

ENG_CVM_CVM_154809-E_1.3d_stp.zip

English

Customer View Model

154809-E

PCB Mount Receptacle, Vertical, Board-to-Board, 80 Position, 1.27 mm [.05 in]
Centerline, Fully Shrouded, Gold (Au), Surface Mount, ERNI SMC



[ENG_CVM_CVM_154809-E_1.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_154809-E_1.3d_igs.zip](#)

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Datasheet - ERNI SMC 1.27mm Connectors](#)

English

[Datasheet - ERNI SMC 1.27mm Connectors](#)

German