

Push button UB series

UB-25NNKS1N



* Photo is a sample image.
Colors and shapes may differ from the real ones.
* Please confirm the actual color and shape with product samples.

Display product drawing

2D DXF



PDF

Purchase

Click here for e-order (set kit product)
of this product

Product introduction	
Rectangular push button switch (UB series), solder terminal type (silver contact): double pole double throw, functional operation: momentary type, switch shape: with flange / without barrier (snap-in), ultra short body type (height 17.5) MM) · Abundant color variations · Characters and symbols can be displayed ° C · Applications: Communication equipment, wireless application equipment, electronic measuring instruments, office equipment automation equipment, consumer electronic equipment, etc. · EU-RoHS directive compliant Model name: UB-25NNKS1N	
Product Summary	
Model name	UB-25NNKS1N
category	Push button
series	UB
Subcategory	Non-illuminated switch
Current capacity for detailed display 1	5A 125V AC
Current capacity for detailed display 2	5A 250V AC
Current capacity for detailed display 3	5A 30V DC
Operating temperature range (°C)	-25 / + 70
Number of poles	2-pole
Function 1	ON- (ON)
Function 2	Momentary
Operation section shape	Sold separately: Long angle 17 × 12
Terminal shape	Solder terminals
Environmental performance	RoHS

Specification change				
No.	category	Overview	date of issue	PDF

352	Specification change	Compliant with the banned substance standards of 10 substances regulated by EU-RoHS Directive Compliant by July 22, 2019	April 26, 2019	
272	Specification change	Transfer of production from Chinese factory to Philippine factory	March 31, 2016	

Function UP accessories

- ▶ Dustproof cover AT-4011 (dustproof cover, frame color: black)
- ▶ Safety guard barrier AT-4172

Total 2 results

To series TOP▶