


Omron Automation & Safety - U.S. Headquarters

2895 Greenspoint Parkway, Suite 200

Hoffman Estates, IL 60169

Tel: +1 (800) 556-6766, +1 (847) 843-7900

Fax: +1 (847) 843-7787

Email: info@omron.com
Item # 44501-3141, Plastic Head Material Tongue Interlock Switch

T5009-6040F1M - Tongue Interlock Switch, 4 Normally Closed (NC) BBM, 3 X 0.5 In. National Pipe Thread (NPT), Plastic With TI8012 Flex Actuator


Specifications

Type	Tongue Interlock Switch
Contact Configuration	4 Normally Closed (NC)
Conduit Size	0.5 in. National Pipe Thread (NPT)
Actuator Type	Flex 1 For TI8012
Actuation Speed (Operating Speed) [Max]	160 mm/s
Conformity and Certifications	EN1088, EN292, EN60947-5-1, EN60204-1, UL508, CE Marked for Applicable Directives, UL, C-UL
Accessories	44526-0801
Spare Parts	44519-0710
Model	T5009-6040F1GN
Head Material	Plastic
Operating Temperature [Min]	-25 °C -13 °F

Operating Temperature [Max]	80 °C 176 °F
IP Rating	IP67
Actuation Frequency [Max]	2 cycles/s
Break Contact Force [Min]	12 N 2.7 lb
Weight	160 g