

1453384

<https://www.phoenixcontact.com/us/products/1453384>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR/PVC, black RAL 9005, free cable end, on Valve connector A, with 1 LED, Wiring: Z diode, cable length: 3 m

Commercial data

Item number	1453384
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF07
Product key	BF1DAA
GTIN	4046356552943
Weight per piece (including packing)	179.4 g
Weight per piece (excluding packing)	176.2 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable



1453384

<https://www.phoenixcontact.com/us/products/1453384>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	3
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Seal material	TPU
Material housing valve plug	TPU
Contact material	CuSn
Valve plug contact insert material	PA 6.6
Contact surface material	Sn

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	4 A

Signaling

Status display	1 LED
Status display present	Yes

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Valve connector A
Material	CuSn (Contact)
	Sn (Contact surface)
	PA 6.6 (Contact carriers)
	TPU (Housing)

Cable/line

Cable length	3 m
--------------	-----

PUR/PVC, 0.75 mm², black [116]

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable



1453384

<https://www.phoenixcontact.com/us/products/1453384>

Dimensional drawing	
Cable weight	53.4 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR/PVC, 0.75 mm², black [116]
Conductor structure signal line	24x 0.20 mm
AWG signal line	18
Conductor cross section	3x 0.75 mm²
Wire diameter incl. insulation	1.7 mm ±0.05 mm
External cable diameter	5.80 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
Max. conductor resistance	26 Ω/km (at 20 °C)
Insulation resistance	≥ 20 MΩ*km
Nominal voltage, cable	300 V
Test voltage	1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	29 mm
Smallest bending radius, movable installation	58 mm
Dynamic load capacity (bending)	Max. bending cycles: 1000000, Traversing path: 10 m, Traversing rate: 2 m/s, Acceleration: 2.5 m/s²
Flame resistance	DIN VDE 0482 DIN EN 50265-2-1 in acc. with UL FT-2
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Low adhesion
Special properties	flexible
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable



1453384

<https://www.phoenixcontact.com/us/products/1453384>

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-20 °C ... 85 °C (valve plug)
	-40 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable


1453384

<https://www.phoenixcontact.com/us/products/1453384>




Drawings

Schematic diagram




Valve connector pin assignment, type A

Dimensional drawing




Valve connector, type A



SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable

1453384

<https://www.phoenixcontact.com/us/products/1453384>



Valve connector, type A, side view

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable



1453384

<https://www.phoenixcontact.com/us/products/1453384>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1453384>

	CSA			
	Approval ID: 13631			
		Nominal voltage U _N	Nominal current I _N	Cross section AWG
		24 V	4 A	-

	CSAus			
	Approval ID: 13631			
		Nominal voltage U _N	Nominal current I _N	Cross section AWG
		24 V	4 A	-

cCSAus

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable



1453384

<https://www.phoenixcontact.com/us/products/1453384>

Classifications

ECLASS

ECLASS-11.0	27060312
ECLASS-12.0	27060312
ECLASS-13.0	27060312

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Diboron trioxide(CAS: 1303-86-2)
	Lead monoxide (lead oxide)(CAS: 1317-36-8)
SCIP	0c8229ac-e67d-407c-89b5-27e844ba8328

SAC-3P- 3,0-116/A-1L-Z - Sensor/actuator cable



1453384

<https://www.phoenixcontact.com/us/products/1453384>

Accessories

SAC-V-SCREW-M3-29 KNURL - Screw

1403779

<https://www.phoenixcontact.com/us/products/1403779>

Fillister head screw with plastic knurl, M3 x 40



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com