

Rear panel feed-through - RC-09S1N12C3X7 - 1596071

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Feed-through of rear wall, straight, shielded: yes, Screw locking, M23, No. of pos.: 8+1, type of contact: Socket, Solder connection, Radial O-ring, 4xM3, Panel thickness max.: 2.5 mm, cable diameter range: 4.5 mm ... 5.5 mm



Key Commercial Data

Packing unit	20 pc
GTIN	4 046356 209687
GTIN	4046356209687

Technical data

Environmental Product Compliance


REACh SVHC	Lead 7439-92-1			
China RoHS	Environmentally Friendly Use Period = 50			
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"			

Drawings

Schematic diagram



Dimensional drawing





Rear panel feed-through - RC-09S1N12C3X7 - 1596071

Approvals			
Approvals			
Approvals			
EAC			
Ex Approvals			
Approval details			
EAC	ERE		B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1596071