

# EVVOSEMI<sup>®</sup>

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

## Product Specification

▶ Domestic	Part Number	SS12F THRU SS120F
▶ Overseas	Part Number	SS12F THRU SS120F
▶ Equivalent	Part Number	SS12F THRU SS120F


EV is the abbreviation of name EVVO

**SS12F THRU SS120F**  
**20V-200V 1A**
**FEATURES**

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

**MECHANICAL DATA**

- Case: SMAF
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 27mg / 0.00095oz



Dimensions in inches and (millimeters)

**Absolute Maximum Ratings and Electrical characteristics**

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %


Parameter	Symbols	SS12F	SS14F	SS16F	SS18F	SS110F	SS112F	SS115F	SS120F	Units
Maximum Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	20	40	60	80	100	120	150	200	V
Maximum RMS voltage	V <sub>RMS</sub>	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V <sub>DC</sub>	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current	I <sub>F(AV)</sub>	1.0								A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I <sub>FSM</sub>	40				30				A
Max Instantaneous Forward Voltage at 1 A	V <sub>F</sub>	0.55		0.70		0.85		0.90		V
Maximum DC Reverse Current   T <sub>a</sub> = 25°C at Rated DC Reverse Voltage   T <sub>a</sub> =100°C	I <sub>R</sub>	0.3 10				0.2 5		0.1 2		mA
Typical Junction Capacitance <sup>(1)</sup>	C <sub>j</sub>	110		80						pF
Typical Thermal Resistance <sup>(2)</sup>	R <sub>θJA</sub>	95								°C/W
Operating Junction Temperature Range	T <sub>j</sub>	-55 ~ +150								°C
Storage Temperature Range	T <sub>stg</sub>	-55 ~ +150								°C

( 1 ) Measured at 1 MHz and applied reverse voltage of 4 V D.C


( 2 ) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

**20V-200V 1A**


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Forward Characteristic**




**Fig.4 Typical Junction Capacitance**



**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**



**Fig.6- Typical Transient Thermal Impedance**



20V-200V 1A

## ORDERING INFORMATION

Order Code	Package	Baseqty	Deliverymode
SS12F	SMAF	3000	Tape and reel
SS14F	SMAF	3000	Tape and reel
SS16F	SMAF	3000	Tape and reel
SS18F	SMAF	3000	Tape and reel
SS110F	SMAF	3000	Tape and reel
SS112F	SMAF	3000	Tape and reel
SS115F	SMAF	3000	Tape and reel
SS120F	SMAF	3000	Tape and reel

## Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.