



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DRC Housings



Connector System: **Wire-to-Wire**

Number of Positions: **24**

Connector & Housing Type: **Housing for Female Terminals**

Centerline (Pitch): **5.49 mm [.216 in]**

Sealable: **Yes**

[All DEUTSCH DRC Housings \(117\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Blank Cavity Position	0
Number of Positions	24
Number of Rows	4

Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	250 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black



Connector & Keying Code	A
-------------------------	---

Contact Features

Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PPS GF
Centerline (Pitch)	5.49 mm[.216 in]

Dimensions

Connector Height	29.16 mm[1.148 in]
Product Width	53.34 mm[2.1 in]
Product Length	40.64 mm[1.6 in]
Row-to-Row Spacing	5.49 mm[.216 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94

Packaging Features

Packaging Quantity	125
--------------------	-----



Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

DRC16-24SA

Housing for Female Terminals, Wire-to-Wire, 24 Position, 5.49 mm [.216 in]
Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DRC



TE Part # CAT-D799-CH8172
DEUTSCH DRC Housings

TE Part # CAT-J67-DSCC16
DEUTSCH Size 16 Crimp Contacts

TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts

TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs

TE Part # CAT-D799-H342
DEUTSCH DRC Headers

TE Part # DRC24-BT
BOOT, 24P, 16SZ, PLG/REC, ST, BLK

TE Part # 0411-291-1405
EXT TOOL, SIZE 16, 14-16 AWG, N, GRN

TE Part # 0411-204-1605
EXT TOOL, SIZE 16, 16-18 AWG, N, DRK BLU

TE Part # 0515-005-2405
PROTECT CVR, 24P, PLG, YEL, DRC16

TE Part # 1062-14-0177
SOC, SF, SIZE 16, 14-18, SN/SN

Also in the Series | **DEUTSCH DRC**

Automotive Housings(117)

Connector Backshells(6)

Connector Strain Relief(3)

Insertion & Extraction Tools(7)

PCB Headers & Receptacles(44)

Customers Also Bought

DRC16-24SA

Housing for Female Terminals, Wire-to-Wire, 24 Position, 5.49 mm [.216 in]
Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DRC



TE Part #DRC16-24SB
DEUTSCH DRC Housings

TE Part #HD10-9-96P-B025
REC, 9P, BLK, N, PANEL, 16

TE Part #DTHD04-1-4P-L009
REC, 1P, BLK, N, SIZE 4, FLANGE

TE Part #2295787-4
STD TIMER PLUG HSG 4P W/EXT. LOCKING

TE Part #1-2176507-4
CJP 200W 6R8 5% Lead

TE Part #626412-2
187 FASTON FLAG REC 20-16 AWG TPBR

TE Part #2819651-1
DT04-3P-EP10

TE Part #881572-2
BUSBAR,STAMPED,CUSN4,0.4MM,3 POSN

Documents

Product Drawings

PLG, 24P, BLK, N, A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DRC16-24SA_99_c-drc16-24sa-99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DRC16-24SA_99_c-drc16-24sa-99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DRC16-24SA_99_c-drc16-24sa-99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Engineering Report

English



[Agency Approvals](#)

[UL Report](#)

English