


Printed-circuit board connector - PTS 1,5/ 2-PH-5,0 BU - 1714876

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug component, Nominal current: 10 A, Rated voltage (III/2): 400 V, Number of positions: 2, Pitch: 5 mm, Connection method: Push-in spring connection, Color: blue, Contact surface: Tin



Key Commercial Data

Packing unit	1
GTIN	 4 055626 370583
GTIN	4055626370583
Custom tariff number	85366990

Technical data

Dimensions

Length	12.8 mm
Height	11.7 mm
Width	10.00 mm
Pitch	5 mm
Dimension a	5.00 mm

General

Number of positions	2
Connection method	Push-in spring connection
Insulating material group	I
Rated voltage (III/2)	400 V
Nominal current I_N	10 A
Flammability rating according to UL 94	V0

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
------------	---

Printed-circuit board connector - PTS 1,5/ 2-PH-5,0 BU - 1714876

Technical data

Environmental Product Compliance

	No hazardous substances above threshold values
--	--

Approvals


Approvals

Approvals

cULus Recognized

Ex Approvals

Approval details

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-20030211
	B	D	
mm²/AWG/kcmil	26-14	26-14	
Nominal current I _N	7 A	7 A	
Nominal voltage U _N	300 V	300 V	