

GRM31M5C2H330JV01#

" # " indicates a package specification code.

To be discontinued

Flow OK

Reflow OK

Complies with RoHS

< List of part numbers with package codes >
GRM31M5C2H330JV01L , GRM31M5C2H330JV01K , GRM31M5C2H330JV01B

Shape



L size	3.2 ± 0.15mm
W size	1.6 ± 0.15mm
T size	1.15 ± 0.1mm
External terminal width e	0.3 to 0.8mm
Distance between external terminals g (Min.)	1.5mm
Size code in mm(inch)	3216 (1206)

References

Packaging	Specifications	Minimum quantity
L	Embossed tape (φ 180mm)	3000
K	Embossed tape (φ 330mm)	10000
B	Packing in bulk	1000

Mass (typ.)	
1 piece	27mg
Reel (φ 180mm)	125.43g

Specifications

Capacitance	33pF ± 5%
Rated voltage	500Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	+25 to +125
Operating temperature range	-55 to +125

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.