

# PRO-S-PS

## 26.5 W TRIPLE OUTPUT POWER SUPPLY ADAPTER

### Overview

The PRO-S Power Supply adapter is a UL approved triple output DC wall mount power adapter with outputs provided through a 5-pin DIN connector.

### Applications

This universal adapter works great for any application needing +5 V, +12 V, or -12 V and a DIN input. It is designed to work with:

- PB-500
- PB-502
- PRO-S-LAB



### Features

- Universal Input
- Built-in EMI filter
- Triple Output
  - +5 VDC
  - +12 VDC
  - -12 VDC



**Global<sup>®</sup>**  
**Specialties**

A Cal Test Electronics Company

22820 Savi Ranch Parkway  
Yorba Linda, CA 92887  
800-572-1028  
[globalspecialties.com](http://globalspecialties.com)

## PRO-S-PS

### Electrical Characteristics

INPUT	
Voltage	90-264 VAC, Universal
Frequency	47-63 Hz
Inrush Current	40 A Typ. Cold start @ 25 °C, 115 VAC
Efficiency	70% Typ. at 120/220 VAC 50/60 Hz input and rated output full load
Line Regulation	± 0.5% output
Maximum Power	26.5 W
Ripple and Noise	
+5 VDC	200 mVpp max
+12 VDC	300 mVpp max
-12 VDC	300 mVpp max
Bandwidth	20 MHz
Capacitance	100 µF across load
OUTPUT CURRENT	
+5 VDC	2.5 A normal, 2.8 A peak
+12 VDC	1.0 A normal, 1.2 A peak
-12 VDC	0.5 A normal, 0.6 A peak

### Mechanical Characteristics

Dimensions	12.1 x 6.1 x 3.5 cm
Weight	350 g

Specifications are subject to change without notice. To ensure the most current version of this datasheet, please download the current version from our website: [globalspecialties.com](http://globalspecialties.com).