



SitemapMasthead

english

Search

HOMEPRODUCTSCATALOGUECOMPANYLATEST NEWSERVICECONTACT0 ARTICLES

Heatsinks f.cool

Profile heatsinks and fluid coolers

- Standard extruded heatsinks
- Extruded heatsinks for lock-in retaining spring
- Extruded heatsinks for PCB mounting
- Extruded heatsinks for DC/DC converter
- Retaining springs for transistors
- U-Extruded heatsinks
- Die-cast heatsinks
- Fin coolers
- Fluid coolers
- Aluminium flat-, quadrangular-, angled-, U- & T-profiles

Heatsinks and active heatsinks for processors

Board Level heatsinks

Cooling aggregates

Accessories for electronic components

Cases f.case

Connectors f.con

You are here: Products » Heatsinks f.cool » Profile heatsinks and fluid coolers » Standard extruded heatsinks » SK 546 ... » SK 546

Standard extruded heatsinks

SK 546 ...

SK 546 150 AL

100 x 10 mm

add to request



Features

Technical Drawing

Service

width

height

plate thickness

length

thermal resistance R_{θ}

surface

100 mm

10 mm

2.5 mm

100 mm

4.45 - 2.5 K/W

raw degreased aluminium



OBERRÜCHTER VEREDLUNG GMBH



ISO 9001



ISO 14001



ISO 27001

Sitemap

Masthead

http://www.fischer-elektronik.de/fisch_elec/CP/heatsinks/VA01/Standard%20extruded%20heatsinks/VA/SK546150AL/index.xhtml

1 / 1