




**Part Number :** [783991011](#)  
**Product Description :** Impact 3 Pair Vertical Power Header, Blades A1 & A2, B1 & B2 5.7mm, Press-Fit, LCP, Glass Filled UL94-V0, Black, Tray Packaging, Lead-Free  
**Series Number :** 78399  
**Status :** Active  
**Product Category :** Backplane Connectors



Documents & Resources


**Drawings**  
[783991011\\_sd.pdf](#)

**3D Models and Design Files**  
[783991011\\_stp.zip](#)  
[SYM-78399-1011-001.zip](#)

**Specifications**  
[AS-76060-9997-001.pdf](#)  
[PS-78213-001-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

- [Multiple Part Product Compliance Statements](#)
- Eu RoHS
  - REACH SVHC
  - Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	Backplane Connectors
Series	78399
Description	Impact 3 Pair Vertical Power Header, Blades A1 & A2, B1 & B2 5.7mm, Press-Fit, LCP, Glass Filled UL94-V0, Black, Tray Packaging, Lead-Free
Application	Mezzanine
Component Type	Power Header
Product Name	Impact
UPC	884982587007

#### Agency

UL	E29179
----	--------

#### Electrical

Current - Maximum per Contact	15.0A
Data Rate	N/A
Shield Type	N/A
Shielded	No
Voltage - Maximum	250V

#### Physical

Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Black
Durability (mating cycles max)	200

First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	2.440/g
Number of Columns	N/A
Number of Pairs	3
Number of Rows	2
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	3.00mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	5.20mm
Pitch - Termination Interface	2.00mm, 3.20mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Polarized to PCB	No
Stackable	No
Temperature Range - Operating	-55° to +85°C
Termination Interface Style	Through Hole - Compliant Pin

## Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

---

## Mates With / Use With

### Mates with Part(s)

Description	Part Number
-------------	-------------

Impact 3 Pair Vertical Power Receptacles	<u>78212</u>
---	--------------