





A-A (10:1)



RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)
(METAL MASK THICKNESS: t=0.15)



- NOTE
- 1 HRS MARK SHALL BE OPTIONAL.
 - 2 LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
 - 3 FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
 - 4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA : GOLD 0.1#m min.				
					LEAD AREA : TIN-PLATING 1#m min.				
					UNDER PLATING : NICKEL 2#m min.				
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA		08.06.30	DRAWING NO.		EDC3-084983-25		
		CHECED : HT. YAMAGUCHI		08.06.28	PART NO.		FX6-80S-0.8SV(71)		
		DESIGNED : TS. MIYAKI		08.06.26	CODE NO.		CL576-0107-4-71		
		DRAWN : TS. MIYAKI		08.06.26			 1/1		