

**MCH5802****DC / DC Converter Applications****Features**

- Composite type with a P-Channel Silicon MOSFET (MCH3308) and a Schottky Barrier Diode (SBS006M) contained in one package facilitating high-density mounting.

[MOSFET]

- Low ON-resistance.
- Ultrahigh-speed switching.
- 4V drive.


[SBD]

- Short reverse recovery time.
- Low forward voltage.

Package Dimensions

unit : mm

2195

**Specifications****Absolute Maximum Ratings** at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
[MOSFET]				
Drain-to-Source Voltage	V _{DSS}		-30	V
Gate-to-Source Voltage	V _{GSS}		±20	V
Drain Current (DC)	I _D		-1	A
Drain Current (Pulse)	I _{DP}	PW≤10μs, duty cycle≤1%	-4	A
Allowable Power Dissipation	P _D	Mounted on a ceramic board (900mm²×0.8mm) 1unit	0.8	W
Channel Temperature	T _{ch}		150	°C
Storage Temperature	T _{stg}		-55 to +125	°C
[SBD]				
Repetitive Peak Reverse Voltage	V _{RRM}		30	V
Nonrepetitive Peak Reverse Surge Voltage	V _{RSM}		30	V
Average Output Current	I _O		0.5	A
Surge Forward Current	I _{FSM}	50Hz sine wave, 1 cycle	10	A
Junction Temperature	T _J		-55 to +125	°C
Storage Temperature	T _{stg}		-55 to +125	°C

Marking : QB


- Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.
- SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

MCH5802

Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
[MOSFET]						
Drain-to-Source Breakdown Voltage	V(BR)DSS	ID=-1mA, VGS=0	-30			V
Zero-Gate Voltage Drain Current	IDSS	VDS=-30V, VGS=0			-1	μA
Gate-to-Source Leakage Current	IGSS	VGS=±16V, VDS=0			±10	μA
Cutoff Voltage	VGS(off)	VDS=-10V, ID=-1mA	-1.2		-2.6	V
Forward Transfer Admittance	yfs	VDS=-10V, ID=-500mA	570	820		mS
Static Drain-to-Source On-State Resistance	RDS(on)1	ID=-500mA, VGS=-10V		430	560	mΩ
	RDS(on)2	ID=-300mA, VGS=-4V		780	1090	mΩ
Input Capacitance	Ciss	VDS=-10V, f=1MHz		80		pF
Output Capacitance	Coss	VDS=-10V, f=1MHz		15		pF
Reverse Transfer Capacitance	Crss	VDS=-10V, f=1MHz		13		pF
Turn-ON Delay Time	tD(on)	See specified Test Circuit		7		ns
Rise Time	tR	See specified Test Circuit		20		ns
Turn-OFF Delay Time	tD(off)	See specified Test Circuit		15		ns
Fall Time	tF	See specified Test Circuit		7		ns
Total Gate Charge	Qg	VDS=-10V, VGS=-10V, ID=-1A		2.6		nC
Gate-to-Source Charge	Qgs	VDS=-10V, VGS=-10V, ID=-1A		0.5		nC
Gate-to-Drain "Miller" Charge	Qgd	VDS=-10V, VGS=-10V, ID=-1A		0.6		nC
Diode Forward Voltage	VSD	IS=-1A, VGS=0		-0.9	-1.5	V
[SBD]						
Reverse Voltage	VR	IR=0.5mA	30			V
Forward Voltage	VF1	IF=0.3A		0.35	0.40	V
	VF2	IF=0.5A		0.42	0.47	V
Reverse Current	IR	VR=10V			200	μA
Interterminal Capacitance	C	VR=10V, f=1MHz		20		pF
Reverse Recovery Time	trr	IF=IR=100mA, See specified Test Circuit.			10	ns

Electrical Connection (Top view)




Switching Time Test Circuit









[MOSFET]











t_{rr} Test Circuit

[SBD]









- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of June, 2001. Specifications and information herein are subject to change without notice.