

S-SM240A

Schottky Barrier Rectifiers

Reverse Voltage 40V Forward Current 2.0A

FEATURES

- * Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- * Low power loss,high efficiency
- * For use in low voltage high frequency inverters, free wheeling,and polarity protection applications
- * Guardring for over voltage protection
- * High temperature soldering guaranteed: 260°C/10 seconds at terminals
- * S- Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

Mechanical Data

Case: JEDEC DO-214AC,
molded plastic


Terminals: Plated axial leads, solderable per
MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.0023 oz., 0.065 g

Handling precaution:None



We declare that the material of product is
Halogen free (green epoxy compound)

1.Electrical Characteristic

Maximum & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol	symbol	S-SM240A	Unit
device marking code		S24	
Maximum repetitive peak reverse voltage	V_{RRM}	40	V
Maximum RMS voltage	V_{RMS}	28	V
Maximum DC blocking voltage	V_{DC}	40	V
Maximum average forward rectified current at TC= 75°C	$I_{F(AV)}$	2.0	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	60	A
Typical thermal resistance (Note 1)	R θ JA	150	°C/W
Operating junction and storage temperature range	TJ, TSTG	-40 to +150	°C

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol	symbol	S-SM240A	Unit
Maximum instantaneous forward voltage at 2.0A	V_F	0.55	V
Maximum DC reverse current TA = 25°C at rated DC blocking voltage TJ = 100°C	IR	0.5 10.0	mA
Typical junction capacitance at 4.0V, 1MHz	CJ	160	PF

NOTES:

1. 8.0mm2 (.013mm thick) land areas

S-SM240A

2. Ratings and Characteristic Curves (TA = 25°C unless otherwise noted)

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-repetitive Peak




Fig 3. - Typical Instantaneous Forward Characteristics




Fig 4. - Typical Reverse Characteristics




Fig 5. - typical transient thermal impedance






Fig 6. - Typical Junction Capacitance




S-SM240A

3. dimension:



Mounting Pad Layout ---SMA





LRC

乐山无线电股份有限公司
Leshan Radio Company, Ltd

S-SM240A

4. Update Record

版次	更新记录	更新作者	更新日期
1	第一版	周杰	2014-4-11
2	印字变更	谭志伟	2017-10-30
3	更新CJ	谭志伟	2020-12-14
C	VF 0.5V变更到0.55V	谭志伟	2021-10-09