# YHVA280-3PXM-A-000 V ACTIVE

TE Internal #: YHVA280-3PXM-A-000

Plug, Cable-to-Cable / Wire-to-Wire, 3 Position, 5.2 mm [.205 in] Centerline, Sealable, Orange, Wire & Cable, Power, Cable Mount

(Free-Hanging)

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings



Connector System: Cable-to-Cable, Wire-to-Wire

Number of Positions: 3

Connector & Housing Type: Plug
Centerline (Pitch): 5.2 mm [ .205 in ]

Sealable: Yes

### **Features**

### **Product Type Features**

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Cable-to-Cable, Wire-to-Wire
Connector & Housing Type	Plug
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	3
Number of Rows	1
Electrical Characteristics	
Operating Voltage	850 VDC
Body Features	
Cable Exit Angle	180°
Primary Product Color	Orange
Connector & Keying Code	A
Contact Features	

2.8mm

Contact Size



Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA66 GF30
Centerline (Pitch)	5.2 mm[.205 in]
Dimensions	
Connector Height	55.3 mm[2.18 in]
Product Width	27.6 mm[1.09 in]
Product Length	32.9 mm[1.29 in]
Jsage Conditions	
Operating Temperature (Max)	140 °C[284 °F]
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]
Operation/Application	
Circuit Application	Power
ndustry Standards	
Degree of Protection	IP6K7, IP6K9K
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Other	
Serviceable	Yes
Connector Position Assurance Capable	Yes

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)  Candidate List Declared Against: JUNE 2024 (241)  SVHC > Threshold:  Octamethylcyclotetrasiloxane (D4) (.5% in Component Part)  Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part)  Decamethylcyclopentasiloxane (D5) (.5% in Component Part)  Article Safe Usage Statements:  Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**





## Customers Also Bought

Plug, Cable-to-Cable / Wire-to-Wire, 3 Position, 5.2 mm [.205 in] Centerline, Sealable, Orange, Wire & Cable, Power, Cable Mount (Free-Hanging)





















## **Documents**

**Product Drawings** 

HVA280-3pxm XE,Key A

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_YHVA280-3PXM-A-000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_YHVA280-3PXM-A-000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_YHVA280-3PXM-A-000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Plug, Cable-to-Cable / Wire-to-Wire, 3 Position, 5.2 mm [.205 in] Centerline, Sealable, Orange, Wire & Cable, Power, Cable Mount (Free-Hanging)



### **HIVONEX CONNECTORS & CHARGING SOLUTIONS**

English

HEMS Sample Kit YHVA280-3pxm-A-000

English

**Product Specifications** 

Application Specification

English