

Item no.:	859-398
Product description:	Rail-mounted terminal block with miniature switching relay RELAY WITH 1 CHANGEOVER CONTACT (1u) WITH MINIATURE SWITCHING RELAY FOR NORMAL SWITCHING POWER RELAY WITH 4 MAKE CONTACTS AND 4 BREAK CONTACTS (4ar)



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Product group	6 (Electronics)
Contact material	AgSnO ₂
Nominal input voltage (Un) (DC)	DC 24 V
Input voltage range	Un ±40 %
Current consumption at UN (20 °C)	14.4 mA
max. switching voltage	AC 250 V
max. continuous current	3 A
Max. switching power (resistive)	AC 750 VA
Max. switching power (resistive)	DC see load limiting value graph
Recommended minimum load	>= 100 mA / AC/DC 12 V
Max. switching load with load / without load	6 min-1 / 20 s-1
Operating power	< 400 mW
Pull-in time (typ)	5 ms
Drop-out time (typ)	6 ms
Bounce time (typ)	5 ms
Normal operating method	100 % ED

Dielectric strength contact / coil (kV)	4 kV
Dielectric strength open contact	1 kV
Dielectric strength contact / coil (1,2/50 µs)	6 kV
nominal voltage per VDE 0110 section 1/4.97, IEC 60 664-1	250 V / 4 kV / 3
Mechanical life	1 x 10 ⁷ switching operations
Mechanical life at max. resistive load AC	3 x 10 ⁴ switching operation



Ambient operating temperature (Un)	-25 °C ... +70 °C
Storage temperature	-40 °C ... +70 °C
Standards	DIN VDE 0160 und IEC60255; DIN VDE 0435 (entspr. Teile); DIN/VDE 0140, DIN EN 61140; DIN VDE 0115 Teil 200; DIN EN 50155
Cross section [mm²]	0.08 - 2.5 mm²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Weight	22.4 g
Color	gray
Wiring type	Front-entry
No. of connection Points	5
No. of potentials	5
Height	56 mm
Height	2.205 in
Width	6 mm
Width	0.236 in
Depth	91 mm
Depth	3.58 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in
Mounting	TS 35

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected