AMP

TE Internal #: 350822-1

Hermaphroditic Contact, Tin, 600 VAC, 600 VDC, 16 – 12 AWG Wire

Size, 1.25 – 2 mm² Wire Size, Crimp, Phosphor Bronze, Power

View on TE.com >



Connectors > Contacts > Connector Contacts











Contact Type: Hermaphroditic

Contact Mating Area Plating Material: Tin

Wire Contact Termination Area Plating Material: Tin

Operating Voltage: 600 VDC

Features

Product Type Features

Discrete Wire Type	Stranded
Sealable	No

Electrical Characteristics

	(00) (00)
Operating Voltage	600 VDC

Contact Features

Wire Contact Termination Area Plating Thickness	2 – 4 μm[79 – 157 μin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Mating Area Plating Material Thickness	2 μm[79 μin]
Contact Mating Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Type	Hermaphroditic
Contact Mating Area Plating Material	Tin
Wire Contact Termination Area Plating Material	Tin
Contact Retention Within Housing	With
Contact Base Material	Phosphor Bronze



Contact Current Rating (Max)	35 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Compatible Insulation Diameter Range	6.86 mm[.27 in]
Wire Size	1.25 – 2 mm ²
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Quantity	250
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought





Documents

Product Drawings

HERM HI/CUR TERM 16-12 LP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_350822-1_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_350822-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_350822-1_E.3d_stp.zip

English

Customer View Model

ENG_CVM_350822-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_350822-1_D.3d_stp.zip

English

Customer View Model

ENG_CVM_350822-1_D.2d_dxf.zip

English



3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Crimping Die Assemblies 90347-2, 90348-2, and 90349-2

English