

# AKG 4 GN - Connection terminal block



3062935

<https://www.phoenixcontact.com/us/products/3062935>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connection terminal block, nom. voltage: 300 V, nominal current: 41 A, connection method: Screw connection, Rated cross section: 4 mm<sup>2</sup>, cross section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting: Neutral busbar, color: green

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3062935             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE73                |
| Product key                          | BE7331              |
| Catalog page                         | Page 554 (C-3-2019) |
| GTIN                                 | 4046356558327       |
| Weight per piece (including packing) | 5.545 g             |
| Weight per piece (excluding packing) | 5.469 g             |
| Customs tariff number                | 85369010            |
| Country of origin                    | IN                  |

# AKG 4 GN - Connection terminal block



3062935

<https://www.phoenixcontact.com/us/products/3062935>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Installation terminal block |
| Number of connections | 1                           |
| Number of rows        | 1                           |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 04 |
|------------------|----|

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Maximum load current                            | 41 A   |
| Maximum power dissipation for nominal condition | 1.02 W |
| Nominal current $I_N$                           | 32 A   |
| Current carrying capacity of the neutral busbar | 140 A  |

### Connection data

|                       |                   |
|-----------------------|-------------------|
| Nominal cross section | 4 mm <sup>2</sup> |
| Maximum load current  | 41 A              |

### Level 1 above 1 below 1

|                                                                                           |                                                       |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------|
| Screw thread                                                                              | M4                                                    |
| Tightening torque                                                                         | 1.5 ... 1.8 Nm                                        |
| Stripping length                                                                          | 16 mm                                                 |
| Conductor cross section rigid                                                             | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>             |
| Cross section AWG                                                                         | 20 ... 10 (converted acc. to IEC)                     |
| Conductor cross section flexible                                                          | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>             |
| Conductor cross section, flexible [AWG]                                                   | 20 ... 12 (converted acc. to IEC)                     |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>             |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>             |
| 2 conductors with same cross section, solid                                               | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, flexible                                            | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>           |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>           |
| Nominal current                                                                           | 41 A                                                  |
| Maximum load current                                                                      | 41 A (with 6 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                                           | 300 V                                                 |
| Nominal cross section                                                                     | 4 mm <sup>2</sup>                                     |

### Dimensions

# AKG 4 GN - Connection terminal block



3062935

<https://www.phoenixcontact.com/us/products/3062935>

|                     |         |
|---------------------|---------|
| Dimensional drawing |         |
|                     |         |
| Width               | 7 mm    |
| Height              | 23.7 mm |
| Depth               | 23.6 mm |
| Length              | 23.7 mm |

## Material specifications

|                                                                         |                  |
|-------------------------------------------------------------------------|------------------|
| Color                                                                   | green (RAL 6021) |
| Flammability rating according to UL 94                                  | V2               |
| Insulating material                                                     | PA               |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C           |
| Relative insulation material temperature index (Elec., UL 746 B)        | 125 °C           |

## Electrical tests

### Temperature-rise test

|                                   |                                |
|-----------------------------------|--------------------------------|
| Requirement temperature-rise test | Increase in temperature ≤ 45 K |
| Result                            | Test passed                    |
| Result                            | Test passed                    |

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Mounting

|               |                |
|---------------|----------------|
| Mounting type | Neutral busbar |
|---------------|----------------|

# AKG 4 GN - Connection terminal block


3062935

<https://www.phoenixcontact.com/us/products/3062935>




## Drawings

Dimensional drawing



Dimensional drawing



# AKG 4 GN - Connection terminal block



3062935

<https://www.phoenixcontact.com/us/products/3062935>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3062935>

|                                                                                                                    |                       |                       |                   |                             |
|--------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>CSA</b><br>Approval ID: 13631 |                       |                       |                   |                             |
|                                                                                                                    | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                    | -                     | 20 A                  | 22 - 12           | -                           |

|                                                                                                                                   |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>EAC</b><br>Approval ID: RU C-DE.BL08.B.00534 |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                  |                       |                       |                   |                             |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>cULus Recognized</b><br>Approval ID: E60425 |                       |                       |                   |                             |
|                                                                                                                                  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                                      |                       |                       |                   |                             |
| Field wiring                                                                                                                     | -                     | 20 A                  | 22 - 12           | -                           |
| Factory wiring                                                                                                                   | -                     | 30 A                  | - 10              | -                           |
| Use group C                                                                                                                      |                       |                       |                   |                             |
| Field wiring                                                                                                                     | -                     | 20 A                  | 22 - 12           | -                           |
| Factory wiring                                                                                                                   | -                     | 30 A                  | - 10              | -                           |
| Use group F                                                                                                                      |                       |                       |                   |                             |
| Field wiring                                                                                                                     | -                     | 20 A                  | 22 - 12           | -                           |
| Factory wiring                                                                                                                   | -                     | 30 A                  | - 10              | -                           |

# AKG 4 GN - Connection terminal block



3062935

<https://www.phoenixcontact.com/us/products/3062935>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141146 |
| ECLASS-12.0 | 27141146 |
| ECLASS-13.0 | 27250116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000001 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31162900 |
|-------------|----------|

# AKG 4 GN - Connection terminal block



3062935  
<https://www.phoenixcontact.com/us/products/3062935>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)