

Features


- High isolation 5000 VRMS
- DC input with zero-cross photo triac output
- Operating temperature range - 40 °C to 100 °C
- REACH & RoHS compliance
- MSL class 1
- Regulatory Approvals
 - UL - UL1577
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1

Applications

- Solenoid/valve controls
- Lighting controls
- Motor controls
- Temperature controls
- Static AC power switches
- Solid state relays
- Interfacing microprocessors to 115 to 240VAC peripherals

Description

The MOC304X, MOC306X and MOC308X series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon random-phase photo triac in a plastic DIP6 package with different lead forming options.



ORDERING INFORMATION

Outline	Part Number	Package	Marking	Packing	Packing Size	Quantity
	MOC304XVPE	DIP6	MOC30XXV /YYWW A	Tube	500mm	65
	MOC306XVPE					
	MOC308XVPE					
	MOC304XVGE	DIP6-M		Tube	500mm	65
	MOC306XVGE					
	MOC308XVGE					
	MOC304XVSE	DIP6-SL		Reel	13 "	1000
	MOC306XVSE					
	MOC308XVSE					

CONTENTS

Pin Configuration And Functions.3

Absolute Maximum Ratings.3

Electrical Optical Characteristics.4

Characteristic Curves.5

Test Circuits.8

Package Dimensions.9

Recommended Solder Mask11

Carrier Tape Specifications12


Ordering And Marking Information13

Reflow Information14

Temperature Profile Of Soldering.15

Disclaimer16

PIN CONFIGURATION AND FUNCTIONS

	Pin	Name
	1	Anode
	2	Cathode
	3	NC
	4	Terminal
	5	Substrate
	6	Terminal

ABSOLUTE MAXIMUM RATINGS

Parameter		Symbol	Value	Unit	Note
INPUT					
Forward Current		I _F	60	mA	
Reverse Voltage		V _R	6	V	
Junction Temperature		T _j	125	°C	
Input Power Dissipation		P _I	100	mW	
OUTPUT					
Off-state Output Terminal Voltage	MOC304X	V _{DRM}	400	V	
	MOC306X		600		
	MOC308X		800		
Peak Repetitive Surge Current PW=100μs, 120pps		I _{TSM}	1	A	
Junction Temperature		T _j	125	°C	
Output Power Dissipation		P _O	300	mW	
COMMON					
Total Power Dissipation		P _{tot}	400	mW	
Isolation Voltage		V _{iso}	5000	V _{rms}	1
Operating Temperature		T _{opr}	-40~100	°C	
Storage Temperature		T _{stg}	-55~125	°C	
Soldering Temperature		T _{sol}	260	°C	2

Note 1. AC For 1 Minute, R.H. = 40 ~ 60%

Note 2. For 10 seconds

ELECTRICAL OPTICAL CHARACTERISTICS(T_a=25°C)

Parameter		Symbol	Min.	Typ.	Max.	Unit	Test Condition	Note
INPUT								
Forward Voltage		V _F	-	1.24	1.4	V	I _F =10mA	
Reverse Current		I _R	-	-	10	μA	V _R =6V	
Input Capacitance		C _{in}	-	8.5	250	pF	V=0, f=1kHz	
OUTPUT								
Peak Off-state Current, Either Direction		I _{DRM}	-	-	100	nA	V _{DRM} =Rated V _{DRM} I _F =0	3
Peak On-state Voltage, Either Direction		V _{TM}	-	1.59	2.5	V	I _{TM} =100mA	
Critical Rate of Rise of Off-state Voltage		dv/dt	1000	-	-	V/μs	V _{PEAK} =Rated V _{DRM}	4
TRANSFER CHARACTERISTICS								
LED Trigger Current	MOC3041 MOC3061,MOC3081	I _{FT}	-	-	15	mA	Terminal Voltage = 3V I _{TM} =100mA	
	MOC3042 MOC3062,MOC3082		-	-	10			
	MOC3043 MOC3063,MOC3083		-	-	5			
Holding Current		I _H	-	237	-	μA		
Isolation Resistance		R _{iso}	10 ¹²	10 ¹⁴	-	Ω	DC500V, 40 ~ 60% R.H.	
Floating Capacitance		C _{io}	-	0.4	-	pF	V=0, f=1MHz	
ZERO-CROSSING CHARACTERISTICS								
Inhibit Voltage		V _{INH}	-	-	20	V	I _F =Rated I _{FT}	
Leakage in Inhibited State		I _{DRM2}	-	-	500	μA	I _F =Rated I _{FT} V _{DRM} =Rated V _{DRM}	

Note3. Test voltage must be applied within dv/dt rating.

Note4. Refer to Fig.15 & Fig.16

CHARACTERISTIC CURVES




Fig.7 Normalized Trigger Current
vs. Ambient Temperature




Fig.8 On-state Terminal Voltage
vs. Ambient Temperature




Fig.9 On-state Terminal Voltage
vs. On-state Terminal Current




Fig.10 Holding Current
vs. Ambient Temperature




Fig.11 Normalized Inhibit Voltage
vs. Ambient Temperature




Fig.12 Normalized Leakage in Inhibit State
vs. Ambient Temperature




Fig.13 Turn On Time
vs. Forward Current






Fig.14 Turn On Time
vs. Ambient Temperature




TEST CIRCUITS




PACKAGE DIMENSIONS


Standard DIP – Through Hole (P Type)



Gullwing (400mil) Lead Forming – Through Hole (M Type)




Surface Mount (Low Profile) Lead Forming (SL Type)




- Dimensions in mm unless otherwise stated

RECOMMENDED SOLDER MASK

Surface Mount (Low Profile) Lead Forming




Surface Mount (Gullwing) Lead Forming



- Dimensions in mm unless otherwise stated


CARRIER TAPE SPECIFICATIONS

Option DIP6-SL




- Dimensions in mm unless otherwise stated


ORDERING AND MARKING INFORMATION

Marking Information			
		MOC : Product Series 30XX : Part Number V : VDE Option / : ISOMICRON YY : Fiscal Year WW : Work Week A : Manufacturing Code	
Order Code			
MOC 30XX X X X Product Series Part Number		Halogen Free E: Halogen-free,Lead-free Z: Halogen, Lead-free Lead Forming P: DIP-Standard G: DIP-M S: SM-SL VDE Option V: VDE approval None	
Packing Quantity			
Option	Quantity	Quantity – Inner box	Quantity – Outer box
DIP-Standard	65 Units/Tube	20 Tubes/Inner box	6 Inner box/Outer box = 7.8k Units
DIP-M	65 Units/Tube	20 Tubes/Inner box	6 Inner box/Outer box = 7.8k Units
SM-SL	1000 Units/Reel	2 Reels/Inner box	5 Inner box/Outer box = 10k Units

REFLOW INFORMATION



TEMPERATURE PROFILE OF SOLDERING



- One time soldering is recommended for all soldering method.
- Do not solder more than three times for IR reflow soldering.

DISCLAIMER

- ISOMICRON is continually improving the quality, reliability, function and design. ISOMICRON reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- ISOMICRON makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, ISOMICRON disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular
- The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Please contact ISOMICRON sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify ISOMICRON's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.