

1812416

<https://www.phoenixcontact.com/us/products/1812416>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Terminator to protect the end of a solar panel trunk line.

Commercial data

Item number	1812416
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	AB05
Product key	ABLWZX
Catalog page	Page 72 (NTK-2014)
GTIN	4046356738699
Weight per piece (including packing)	24.5 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	39269097
Country of origin	US

PV-MI-CABLE TERMINATOR 3P - Termination block



1812416

<https://www.phoenixcontact.com/us/products/1812416>

Technical data

Product properties

Product type	Shroud
Number of positions	3

Electrical properties

Rated voltage (III/3)	600 V AC/DC
-----------------------	-------------

Dimensions

Wrench size, union nut	22.00 mm
------------------------	----------

External dimensions

Outside diameter	9.5 mm ... 13 mm (0.37" ... 0.51")
------------------	------------------------------------

Material specifications

Color	black
Material for screw connection	EPCM

Cable/line

Cable type	TC-ER
External cable diameter	9.5 mm ... 13 mm
Single wire, number of litz wires	3
Wire diameter incl. insulation	4.5 mm (max.)

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	10 (with same cable diameter)
-----------------------------	-------------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-40 °C ... 90 °C

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

PV-MI-CABLE TERMINATOR 3P - Termination block



1812416

<https://www.phoenixcontact.com/us/products/1812416>

Accessories

PV-MI-CABLE SPLICE 3P - Housing

1812403

<https://www.phoenixcontact.com/us/products/1812403>



Housing to protect splice connection of solar panel wires. Allows splice of 3 conductors (1.5 to 25 mm²/16 to 4 AWG maximum) to be inside housing with an IP67 rating.

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com