

Part Number: 1731130083

Product Description: FCT High-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 15 Circuits

Series Number: 173113

Status: Active

**Product Category:** D-Sub Connectors **Engineering Number: CT09-15S1** 



#### **Documents & Resources**

**Specifications** 

1731120006-PK-000.pdf

### **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

# **Part Details**

## General

Status	Active
Category	D-Sub Connectors
Series	173113
Description	FCT High-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 15 Circuits
IP Rating	IP20
Magnetic	Yes
Product Name	FCT Products
Туре	High Density
UPC	889056489966

### Electrical

Current - Maximum per Contact	3.0A
Shielded	Yes

# Physical

Circuits (Loaded)	15
Circuits (Loaded)	13
Circuits (maximum)	15
Color - Resin	Black
Durability (mating cycles max)	50
Gender	Female
Material - Contact	Copper Alloy
Material - Resin	PBT
Material - Shell	Steel
Net Weight	6.000/g
Number of Rows	3
Orientation	Straight
Packaging Type	Tray
Panel Mount	Rear

Panel Mount Method	Flange
PC Tail Length	9.50mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	1.98mm
Pitch - Termination Interface	1.98mm
Plating - Contact	Gold over Nickel
Plating - Shell	Nickel
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	1
Temperature Range - Operating	-55° to +105°C
Termination Style	Through Hole
Waterproof / Dustproof	No
Waterproof / Dustproof Type	IP20

# Mates With / Use With

## Mates with Part(s)

Description	Part Number
Mates With	FCT High-Density D-Sub, Size 1, 15 Position, Plug

This document was generated on Oct 31, 2024