




**Part Number :** [1502000012](#)  
**Product Description :** Ditto Hermaphroditic Crimp Terminal, Copper Nickel, Select Gold Plating, 26-24 AWG, for High-Temperature (-40° to +150°C) Housing  
**Series Number :** 150200  
**Status :** Active  
**Product Category :** Crimp Terminals




Documents & Resources

**Drawings**  
[1502000012\\_sd.pdf](#)  
[PK-150197-0000-000.pdf](#)

**Specifications**  
[1502000000-AS-000.pdf](#)  
[1502000000-PS-000.pdf](#)  
[1502000000-TS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	Crimp Terminals
Series	150200
Description	Ditto Hermaphroditic Crimp Terminal, Copper Nickel, Select Gold Plating, 26-24 AWG, for High-Temperature (-40° to +150°C) Housing
Application	Power, Wire-to-Wire
Comments	See Product Specification for maximum current rating by circuit size and AWG.
Product Name	Ditto
UPC	191130037780

#### Electrical

Current - Maximum per Contact	6.0A
Voltage - Maximum	350V AC/DC

#### Physical

Durability (mating cycles max)	100
Gender	Hermaphroditic
Material - Metal	Copper Nickel
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	0.115/g
Packaging Type	Reel
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.05-1.50mm
Wire Size (AWG)	24, 26

Wire Size mm <sup>2</sup>	N/A
---------------------------	-----

Use with Part(s)

Description	Part Number
Ditto Hermaphroditic Crimp Housings	<u>150201</u>

Application Tooling

Global

Description	Part Number
Extraction Tool for SPOX, MX64, Ditto, MX150CE, Milli-Grid Terminals	<u>638131400</u>
Hand Crimp Tool for Ditto Wing Hermaphroditic Interconnects Terminal, 26-24 AWG	<u>638278600</u>
FineAdjust Applicator for Ditto Hermaphroditic Crimp Terminals, 26-24 AWG	<u>639048400</u>