

Description

The SX420N06T uses advanced technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 10V. This device is suitable for use as a Battery protection or in other Switching application.

General Features


$V_{DS} = 60V$ $I_D = 300A$

$R_{DS(ON)} < 2.0m\Omega$ @ $V_{GS}=10V$


Application

Battery protection

UPS



TO-263-3L



Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	60	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D@T_c=25^\circ\text{C}$	Continuous Drain Current ^{1,6}	420	A
$I_D@T_c=100^\circ\text{C}$	Continuous Drain Current ^{1,6}	238	A
IDM	Pulsed Drain Current ²	1340	A
EAS	Single Pulse Avalanche Energy ³	580	mJ
IAS	Avalanche Current	47	A
$P_D@T_c=25^\circ\text{C}$	Total Power Dissipation ⁴	231	W
TSTG	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	62.5	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	0.65	$^\circ\text{C/W}$

Electrical Characteristics (T_J=25°C, unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Type	Max	Unit
V(BR)DSS	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	60	66	-	V
IGSS	Gate-body Leakage Current	V _{DS} = 0V, V _{GS} = ±20V	-	-	±100	nA
IDSS T _J =25°C	Zero Gate Voltage Drain Current	V _{DS} = 60V, V _{GS} = 0V	-	-	1	μA
IDSS T _J =100°C	Zero Gate Voltage Drain Current		-	-	100	
VGS(th)	Gate-Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	2.0	2.9	4.0	V
RDS(on)	Drain-Source On-Resistance ⁴	V _{GS} = 10V, I _D = 20A	-	1.8	2.0	mΩ
gfs	Forward Transconductance ⁴	V _{DS} = 5V, I _D = 20A	-	97	-	S
Ciss	Input Capacitance	V _{DS} = 30V, V _{GS} = 0V, f = 1MHz	-	7312	-	pF
Coss	Output Capacitance		-	2239	-	
Crss	Reverse Transfer Capacitance		-	53	-	
RG	Gate Resistance	f = 1MHz	-	3.0	-	Ω
Qg	Total Gate Charge	V _{GS} = 10V, V _{DS} = 30V, I _D = 20A	-	102	-	nC
Qgs	Gate-Source Charge		-	25	-	
Qgd	Gate-Drain Charge		-	15.8	-	
td(on)	Turn-on Delay Time	V _{GS} = 10V, V _{DD} = 30V, R _G = 3Ω, I _D = 20A	-	24	-	ns
t _r	Rise Time		-	71	-	
td(off)	Turn-off Delay Time		-	129	-	
t _f	Fall Time		-	92	-	
t _{rr}	Body Diode Reverse Recovery Time	I _F = 20A, dI/dt = 100A/μs	-	86	-	ns
Q _{rr}	Body Diode Reverse Recovery Charge		-	61	-	nC
VSD	Diode Forward Voltage ⁴	I _S = 20A, V _{GS} = 0V	-	-	1.2	V
IS	Continuous Source Current T _C =25°C		-	-	300	A

Note :

- 1、The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2、The data tested by pulsed , pulse width .The EAS data shows Max. rating .
- 3、The power dissipation is limited by 175°C junction temperature
- 4、EAS condition: T_J=25°C , V_{DD}=48V, V_G=10V, R_G=25Ω, L=0.1mH, I_{AS}= 55A
- 5、The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation.

Typical Characteristics




Figure 1: Saturation Characteristics




Figure 2: Transfer Characteristics




Figure 3: $R_{DS(ON)}$ vs. Drain Current




Figure 4: $R_{DS(ON)}$ vs. Junction Temperature




Figure 5: $V_{GS(th)}$ vs. Junction Temperature




Figure 6: $V_{BR(DSS)}$ vs. Junction Temperature

Typical Characteristics




Figure 7: Body-Diode Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Current De-rating




Figure 10: Power De-rating




Figure 11: Single Pulse Power Rating, Junction-to-Case




Figure 12: Maximum Safe Operating Area

Typical Characteristics





Figure 13: Normalized Maximum Transient Thermal Impedance

Package Mechanical Data-TO-263-3L-SLK


Symbol	Common		
	mm		
	Mim	Nom	Max
A	4.35	4.47	4.60
A1	0.09	0.10	0.11
A2	2.30	2.40	2.70
b	0.70	0.80	1.00
b2	1.25	1.36	1.50
C	0.45	0.50	0.65
C1	1.29	1.30	9.40
D	9.10	9.20	9.30
D1	7.90	8.00	8.10
E	9.85	10.00	10.20
E1	7.90	8.00	8.10
H	15.30	15.50	15.70
e	-	2.54	-
L	2.34	2.54	2.74
L1	1.00	1.10	1.20
L2	1.30	1.40	1.50
R	0.24	0.25	0.26
θ	0°	4°	8°
θ1	4°	7°	10°
θ2	0°	3°	6°

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
TAPING	TO-263-3L		800