

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.03.31	阿树

Specifications:
规格:
Voltage rating: 50V AC/DC
额定电压: 50V AC/DC
Current rating: 1A AC/DC
额定电流: 1A AC/DC
Contact resistance: 20mΩ Max
接触电阻: 20mΩ Max
Insulation resistance: 100MΩ min
绝缘电阻: 100MΩ Min
Withstanding voltage: 250V AC/minute
耐受电压: 250V AC/分钟
Temperature range: -40℃~+125℃
温度范围: -40℃~+125℃
Cycles: 12000
寿命: 12000

PART NO.:

X1254 T-P XX
① ② ③ ④

- ①Series Number.
- ②Category: T-terminal
- ③Material: P-Phosphor bronze
- ④Plating: XX: V01-Gold Plated
SN-Tin Plating

X1254T-PV01	Phosphor bronze	AWG#28~32	1.0mm (MAX)	Stamping Pating: 30u"Ni Whole Gold Flash	X1254H
X1254T-PSN				Stamping Before Pating: 30u" Ni 70U"Sn Min	
PART NO	Material	Wire Range	Insulation O.D	Wire Range	Suitable XKB Housing

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树	VIEW:	
CHECKED		UNIT:	mm/in
APPROVED		SIZE:	A4

MODEL TYPE:	1.25mm Crimp Style Connector
PART NO.:	X1254T-PSN
DWG NO.:	

SCALE	PAGE	REVISION
N/A	1/1	A1

XKB INDUSTRIAL PRECISION CO.,LIMITED