

Part Number: 1552210004

**Product Description :** Flamar Sensor Cable, WSOR Jacket, Braided Shielding Overall, 3 Circuits, 0.34mm<sup>2</sup> / 22 AWG, 5.40mm (.213") Diameter, 600.0m (1968.50') Length, Gray

Status: Obsolete

**Engineering Number: 3X200M** 

Series Number: 155221

**Product Category:** Industrial Cable

#### **Documents & Resources**

## **Product Environment Compliance**

#### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

#### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

#### **Part Details**

#### General

Status	Obsolete
Category	Industrial Cable
Series	155221

Description	Flamar Sensor Cable, WSOR Jacket, Braided Shielding Overall, 3 Circuits, 0.34mm² / 22 AWG, 5.40mm (.213") Diameter, 600.0m (1968.50') Length, Gray
Comments	3 reels of 200.0m each
Geographic Area	Global
Product Family	Flamar Standard and Custom Cables for Industrial Automation
Product Name	Flamar,Signal and Control
UPC	889056463669

## Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

# Physical

Bending Radius - Minimum	> 7.5xOD
Cable Length	600.0m
Circuits (Loaded)	3
Color - Cable Jacket	Gray
Insulation	TPE
Material - Outer Jacket	WSOR
Net Weight	0.010/g
Outer Jacket Diameter	5.40mm
Packaging Type	Reel
Temperature Range - Operating	-25° to +80°C
Wire/Cable Type	UL AWM 21215 / CSA
Wire Size (AWG)	22
Wire Size mm²	0.34