





Miniature circuit breaker 230 V 10kA, 1+N-pole, C, 6A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	2
design of pole	1P+N
tripping characteristic class	C
mechanical service life (operating cycles)	
• typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui)	
• with single-phase operation at AC rated value	250 V
operational current	
• at 30 °C rated value	6 A
• at 40 °C rated value	5.68 A
• at 55 °C rated value	5.17 A
• at AC rated value	6 A
Supply voltage	
supply voltage at AC	230 V
value range of the supply voltage frequency	50/60 Hz
operating voltage	
• at DC rated value maximum	72 V
Protection class	
protection class IP	IP20, with connected conductors
Breaking Capacity	
switching capacity current	
• according to EN 60898 rated value	10 kA
• according to IEC 60947-2 rated value	10 kA
energy limitation class	3
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	1.6 W
suitability for operation	Residential buildings/infrastructure
Product details	
product feature	
• halogen-free	Yes
• sealable	Yes

• silicon-free	Yes				
product extension installable supplementary devices	Yes				
Connections					
connectable conductor cross-section solid					
• minimum	0.75 mm ²				
• maximum	25 mm ²				
connectable conductor cross-section stranded					
• minimum	0.75 mm ²				
• maximum	25 mm ²				
connectable conductor cross-section finely stranded with core end processing					
• minimum	0.75 mm ²				
• maximum	25 mm ²				
tightening torque with screw-type terminals					
• minimum	2.5 N·m				
• maximum	3 N·m				
Mechanical Design					
height	90 mm				
width	36 mm				
depth	76 mm				
installation depth	70 mm				
number of modular width units	2				
mounting position	any				
net weight	304 g				
Environmental conditions					
ambient temperature during operation					
• minimum	-25 °C				
• maximum	55 °C				
ambient temperature during storage					
• minimum	-40 °C				
• maximum	75 °C				
Approvals Certificates					
General Product Approval					
			Confirmation		
General Product Approval	Test Certificates	other	Environment		
	Miscellaneous	Miscellaneous	Miscellaneous	Confirmation	Environmental Confirmations
Environment					
Environmental Confirmations					
Further information					
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875					
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs					
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL4506-7					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/5SL4506-7					





last modified:

7/6/2024 

