

### Power Double Lock

TE Internal #: 5-1903720-1

Housing, Cap, Wire-to-Wire, 12 Position, 3.96 mm [.156 in]

Centerline, Wire & Cable, UL 94V-0, Power Double Lock,

Rectangular Power Connectors

View on TE.com >




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire Power Double Lock Cap











Rectangular Power Connector Type: Housing

Connector & Housing Type: Cap Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 3.96 mm [ .156 in ]

All Glow Wire Power Double Lock Cap (35)

## **Features**

## **Product Type Features**

| Connector & Housing Type  Connector System  Wire-to-Wire  Sealable  No | Rectangular Power Connector Type  | Housing      |
|--|-----------------------------------|--------------|
| Sealable No  | Connector & Housing Type          | Сар          |
|  | Connector System                  | Wire-to-Wire |
|  | Sealable                          | No           |
| Connector & Contact Terminates To Wire & Cable                         | Connector & Contact Terminates To | Wire & Cable |

## **Configuration Features**

| Number of Positions        | 12 |
|----------------------------|----|
| Number of Power Positions  | 12 |
| Number of Signal Positions | 0  |
| Number of Rows             | 3  |

## **Electrical Characteristics**

| Operating Voltage | 300 VAC |
|-------------------|---------|



## **Contact Features**

| Contact Type                       | Tab                        |
|------------------------------------|----------------------------|
| Termination Features               |                            |
| Termination Method to Wire & Cable | Crimp                      |
| Mechanical Attachment              |                            |
| Connector Mounting Type            | Cable Mount (Free-Hanging) |
| Housing Features                   |                            |
| Centerline (Pitch)                 | 3.96 mm[.156 in]           |
| Housing Color                      | Natural                    |
| Housing Material                   | Nylon 6/6                  |
| Usage Conditions                   |                            |
| Operating Temperature Range        | -30 - 105 °C[-22 - 221 °F] |
| Operation/Application              |                            |
| Circuit Application                | Power                      |
| Industry Standards                 |                            |
| UL Flammability Rating             | UL 94V-0                   |
| Glow Wire Rating                   | GWT 750°C (Without Flame)  |
| Packaging Features                 |                            |
| Packaging Quantity                 | 150                        |

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability                     | Not reviewed for solder process capability  |

Bag



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**




4POS





# Also in the Series | Power Double Lock







Connector Hardware(14)



Insertion & Extraction Tools(2)



Rectangular Power Connectors(283)

# Customers Also Bought





















## **Documents**

## **Product Drawings**

PDL 3.96MM PITCH CAP HSG 12P NAT(GWT)

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-1903720-1\_F.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1903720-1\_F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1903720-1\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English