

Part Number: 330113004

Product Description: MX150 Male Terminal for Mat-Sealed or Unsealed Connectors, Silver Plating, Grip Code M3, Left Reel Payoff, Contact Material Thickness 0.30mm, Preferred Terminal for use in Sealed Application with 0.35-0.50mm²

Status: Active

Series Number: 33011

Product Category: Crimp Terminals

Documents & Resources

Drawings

Drawing 330113004_sd.pdf

Specifications

Application Specification AS-33000-001-001.pdf Test Summary TS-33000-002-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44; 34; 33 |
|--------------------|--|
| China RoHS | • |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| Status | Active |
|----------------|---|
| Category | Crimp Terminals |
| Series | 33011 |
| Description | MX150 Male Terminal for Mat- Sealed or Unsealed Connectors, Silver Plating, Grip Code M3, Left Reel Payoff, Contact Material Thickness 0.30mm, Preferred Terminal for use in Sealed Application with 0.35-0.50mm ² |
| Application | Power, Wire-to-Board, Wire-to- Wire, Automotive |
| Comments | Left Reel Payoff |
| Product Family | MX150 Sealed and Unsealed Connector System |
| Product Name | MX150 |
| UPC | 884982250604 |

Electrical

| Current - Maximum per Contact | Contact Molex |
|-------------------------------|---------------|
| Voltage - Maximum | 14V DC |

Physical

| Gender | Male |
|--------------------------------|------------------------------|
| Grip Code | M3 |
| Material - Metal | High Performance Alloy (HPA) |
| Material - Plating Mating | Silver |
| Material - Plating Termination | Tin |
| Net Weight | 0.300/g |
| Packaging Type | Reel |
| Plating min - Mating | 0.762µm |
| Plating min - Termination | 0.508µm |
| Termination Interface Style | Crimp or Compression |

| Wire Insulation Diameter | 1.70mm max. |
|---------------------------|-------------|
| Wire Size (AWG) | N/A |
| Wire Size mm ² | 0.35-0.50 |

Use with Part(s)

| Description | Part Number |
|--|--------------|
| MX150 Mat-Sealed Single Row Male Connector Assemblies | <u>33481</u> |
| MX150 Mat-Sealed Dual Row Male Connector Assemblies | 33482 |

Application Tooling

Global

| Description | Part Number |
|--|------------------|
| Extraction Toolkit for MX150 Connectors | 2002220700 |
| FA2 Mechanical Feed Crimp Applicator for MX150 Male Terminals, 0.35mm² and 0.50mm² ISO Wire | <u>638082400</u> |
| FA2 Pneumatic Feed Crimp Applicator for MX150 ISO (M3) Male Terminals, 0.35mm² and 0.50mm² ISO wire | 638082410 |
| Extraction Tool for MX150L, MX150, PT Bulb Socket, iGrid, SPOX, and Wire-to-Motor Terminals | <u>638131500</u> |
| Hand Crimp Tool for ISO (M3) Blade Terminals | 638233600 |
| FineAdjust Applicator for SRC Connector using MX150 (M3) Blade Terminals, 0.50mm² wires | 639041300 |