

Part Number : 511910300

Series Number: 51191

Product Description: 2.50mm Pitch Mini-Latch Wire-to-Wire and Wire-to-Board Receptacle Housing, with Guide Rails, 3

Circuits

Status: New Business Not Supported

Product Category: Connector Housings

Documents & Resources

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | New Business Not Supported |
|----------|----------------------------|
| Category | Connector Housings |

| Series | 51191 |
|----------------|--|
| Description | 2.50mm Pitch Mini-Latch Wire-to- Wire and Wire-to-Board Receptacle Housing, with Guide Rails, 3 Circuits |
| Application | Signal, Wire-to-Board, Wire-to-Wire |
| Product Family | Mini-Latch Wire-to-Board / Wire-to- Wire Connector System |
| Product Name | Mini-Latch |
| UPC | 800753327726 |

Agency

| UL | E29179 |
|----|--------|
|----|--------|

Physical

| Circuits (maximum) | 3 |
|-------------------------------|----------------|
| Flammability | 94V-0 |
| Gender | Receptacle |
| Glow-Wire Capable | No |
| Material - Resin | Nylon |
| Net Weight | 362.200/mg |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 2.50mm |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |