



THE PRODUCT

The OKW DESK CASE range covers many different fields of application. Choose a case that will fully meet your specific requirements in terms of size and tilt of the control panel.

Front panel versions are available for the installation of complete prefabricated electronics units.

YOUR ADVANTAGE

Various angles of inclination for the control panel, depending on requirements. Practical for operating and reading off the unit.

Suitable for numeric keypads and membrane keyboards.

Prepared for the assembly of eurocards 100 x 160 (138/190/190F/190H).

Versions with ample space for large assemblies.

Raised section giving space for easy installation of cable grommets and plug connectors (220, COMBI DESK CASE F/H).

Version with attachment for digital readouts, measuring equipment, encoders etc. (COMBI DESK CASE H).

APPLICATIONS

Systems for data collection on the job and machines. Communications equipment. Access and security controls, data systems engineering.

Medical and laboratory technologies.

Industrial control systems.


Point-of-sale.

PROTECTION CLASS < IP 40

MAX. SIZE OF PCB

DESK CASE/ COMBI-DESK	W x D in inches	
	bottom part	top part
138	4.646 x 7.087	5 x 6.890
190...	7.087 x 4.646	6.890 x 5
220	8.268 x 5.787	—
F/H	8.268 x 7.717	—

(cutouts for pillars not taken into consideration)



ENCLOSURES

DESK CASE	Outside dim. in inches			Equipment (dim. in inches)		Color	Material	Part-No.
	W	D	H	front panel	max. dim. keypad			
138	5.433	7.480	2.126/1.260	—	4.713 x 6.543 (r = 0.157)	off-white	ABS (UL 94 HB)	A 05 14 007
	5.433	7.480	2.126/1.260	—	4.713 x 6.543 (r = 0.157)	black	ABS (UL 94 HB)	A 05 14 009
190	7.480	5.433	1.850/1.260	—	6.752 x 4.571 (r = 0.157)	off-white	ABS (UL 94 HB)	A 05 19 007
	7.480	5.433	1.850/1.260	—	6.752 x 4.571 (r = 0.157)	black	ABS (UL 94 HB)	A 05 19 009
190 F	7.480	5.433	1.850/1.240	• (accessory)	—	pebble gray/off-white	ABS (UL 94 HB)	A 90 86 265
190 H	7.480	5.433	2.756/2.146	• (accessory)	—	pebble gray/off-white	ABS (UL 94 HB)	A 90 86 365
220	8.661	6.142	3.937/2.047	• (accessory)	—	pebble gray/off-white	ABS (UL 94 HB)	A 90 82 065

COMBI DESK CASE	Outside dim. in inches			Equipment		Color	Material	Part-No.
	W	D	H	front panel/s	attachment			
F	8.976	8.504	2.992/1.969	• (accessory)	—	pebble gray/off-white	ABS (UL 94 HB)	A 90 84 165
H	8.976	8.504	4.961/1.969	• (accessory)	• (clip into)	pebble gray/off-white	ABS (UL 94 HB)	A 90 85 165

ACCESSORIES (wall suspension element for DESK CASES 138/190 see accessories page 103)

Article	For enclosure	Version / Application	Part-No.
	190 F/H	matt anodized aluminum 6.358" x 4.173" x 0.059" (screws supplied with case)	A 91 86 001
	220	matt anodized aluminum 8.091" x 5.094" x 0.059" (screws supplied with case)	A 91 80 001
	F/H	matt anodized aluminum 7.874" x 5.118" x 0.059" (screws supplied with case)	A 91 84 001
	H (attachment)	matt anodized aluminum 7.874" x 1.378" x 0.059" (screws supplied with case)	A 91 85 001

DATEC-KEYBOARD

The DATEC-KEYBOARD represents an almost indestructible case system for stationary data collection. The double-walled case construction provides the necessary stability for applications in rough conditions.

Flat areas for individual application and cutouts. Working without getting tired. Ergonomic design. The standard feet can be adjusted to different inclination angles (included). Holes on the bottom side of the cases allow direct mounting to a wall or machinery.



ENCLOSURES

DATEC-KEYBOARD	Outside dim. in inches			max. dim. keypad	Equipment (dim. in inches)	Material	Part-No.	
	W	D	H				off-white	black
S	13.386	9.449	1.575	12.173 x 6.512	•	ABS (UL 94 HB)	A 05 34 107	A 05 34 109
L	19.291	9.449	1.575	18.071 x 6.512	•	ABS (UL 94 HB)	A 05 49 107	A 05 49 109

ACCESSORIES

Article	Version / Application	Part-No.
Sealing kit	for sealing up to IP 65, 1 O-ring for the case	S L A 91 34 001 A 91 49 001

KEYBOARD HOUSINGS

These KEYBOARD HOUSINGS have been developed according to ergonomic guidelines for VDU work stations. They are flat and practical, thus permitting pleasant handling as control units.

With predetermined openings for round cables with traction discharge, flange socket and 15-channel subminiature plug. Working without getting tired. Ergonomic design. With/without deposit groove. Providing more space for additional key blocks, function keys, digital readouts.



ENCLOSURES

KEYBOARD HOUSING	Outside dim. in inches			Version / Equipment (dim. in inches)		Material	Part-No. off-white
	W	D	H	with deposit groove			
370	14.567	7.283	1.476	I	13.307 x 0.984	ABS (UL 94 HB)	A 05 37 407
	14.567	7.283	1.476	II	—	ABS (UL 94 HB)	A 05 37 007