

Part Number: 2065230163

Product Description: Mini50 Unsealed Receptacle, Dual Row, UL94-HB, without CPA, 16 Circuits, Polarization Option A, Black

Series Number: 206523

Status: Active

Product Category: Connector Housings



Documents & Resources

Drawings

Drawing 2065230163_sd.pdf
Packaging Design Drawing PK-31301-538-001.pdf
Packaging Design Drawing PK-31301-538-001.pdf

3D Models and Design Files

3D Model 2065230163_stp.zip

Specifications

Product Specification 2065230000-PS-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant |
|--------------------|--|
| China RoHS | • |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Connector Housings |
| Series | 206523 |
| Description | Mini50 Unsealed Receptacle, Dual Row, UL94-HB, without CPA, 16 Circuits, Polarization Option A, Black |
| Application | Automotive, Power, Wire-to-Board |
| Product Family | Mini50 Connection Systems |
| Product Name | Mini50 |
| UPC | 191130110032 |

Physical

| Circuits (maximum) | 16 |
|-------------------------------|-------------|
| Color - Resin | Gray (Dark) |
| Gender | Receptacle |
| Glow-Wire Capable | No |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Resin | PBT |
| Net Weight | 1.687/g |
| Number of Rows | 2 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 2.00mm |
| Pitch - Termination Interface | 2.00mm |
| Polarization | С |
| Polarized to Mating Part | Yes |

| Stackable | No |
|-------------------------------|----------------|
| Temperature Range - Operating | -40° to +100°C |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--|------------------|
| Mini50 Unsealed Header, Right- Angle, SMT, Dual Row, 16 Circuits, Tin (Sn) Plating, Polarization Option C, Dark Gray, Tape and Reel | <u>348978162</u> |
| Mini50 Unsealed Header, Right- Angle, SMT, Dual Row, 16 Circuits, Tin (Sn) Plating, Polarization Option C, Dark Gray, Tube | <u>348979162</u> |
| Mini50 Unsealed Vertical Header, Dual Row, 16 Circuit, Polarization Option C, Dark Gray, Tray | <u>348250162</u> |
| Mini50 Unsealed Vertical Header, Dual Row, 16 Circuit, Polarization Option C, Dark Gray, Tube | <u>348259162</u> |
| Mini50 Unsealed Right-Angle Header, Dual Row, 16 Circuit, Polarization Option C, 2.80mm Pin Length, Dark Gray, Tray | <u>348260162</u> |
| Mini50 Unsealed Right-Angle Header, Dual Row, 16 Circuit, Polarization Option C, 2.80mm Pin Length, Dark Gray, Tube | 348269162 |

Use with Part(s)

| Description | Part Number |
|--|---------------|
| CTX50 Unsealed Receptacle Terminals | <u>560023</u> |