



Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window



△數 COUNT	訂正事項 DESCRIPTION OF REVISIONS		擔當 B Y	檢圖 CHKD	年月日 DATE	△數 COUNT	訂正事項 DESCRIPTION OF REVISIONS		擔當 B Y	檢圖 CHKD	年月日 DATE
△1	1	RE-6-1150	K.I.Y	L.S.M	18. 07. 04	△					. .
△2	2	RE-6-1579	K.I.Y	L.S.M	20. 01. 23	△					. .
△					. .	△					. .


RECOMMENDED LAND PATTERN (FREE)
(PCB THICKNESS t=1.6mm)



ENGAGEMENT FIGURE (2:1)

NOTE 1. 1PACK CONTAINS 100PCS.
2. ()DIMENSIONS ARE ONLY REFERENCE.
3. UL(File No. E132750) AUTHORIZATION ARTICLE.
C-UL(File No. E132750) AUTHORIZATION ARTICLE.



1	 PA66	UL94V-0, BLACK	2	BRASS	GOLD PLATING 0.1μm MIN, OVER NICKEL 0.5μm MIN		
NO.	MATERIAL	FINISH,REMARKS	NO.	MATERIAL	FINISH,REMARKS		
CODE NO. (OLD)			DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
			CHOI 17.12.22 J.S	CHOI 17.12.22 J.S	LIM 17.12.22 S.M	KANG 17.12.22 T.S	ENG 20.02.12 DEPT
	DRAWING NO.		PART NO.				
SCALE	EDC3-632469		DF51K-28DP-2DSA (805)				
5:1							
UNITS	HRS HIROSE KOREA CO.,LTD.		CODE NO.				
mm			CL 6652-0018-4 -805				
			1/1				