

Search Results

- Evaluate
- FAQ's
 - Selection Guides
 - PDF Convenience..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) [Search Tips](#)

 Text Search: 'PN18-6F-E'

Your search criteria matched only one product, shown below

PN18-6F-E



- Fork design provides for fast and easy installation, without the need to remove fastener
 - Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
 - Internal barrel serrations assure good wire contact and maximum tensile strength
 - UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
 - UL and CSA rated up to 600 V per UL 486A/B, where applicable
- ‡UL and CSA approved tooling/product combinations.
Note: Wire sizes #26 – #22 AWG, are not UL Listed or CSA Certified.

▪ Part Number	PN186F-E
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Fork Terminal, nylon insulated, 22- 18 AWG, #6 stud size.
▪ Product Type	Terminals
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ Length (In.)	0.78
▪ Length (mm)	19.8
▪ Width (In.)	0.30
▪ Width (mm)	7.6
▪ CE Compliant	No
▪ Clearance	0.20
▪ Clearance (mm)	5.1
▪ Insulation	Nylon
▪ Max. Ins.	0.145
▪ Max. Ins. (mm)	3.75
▪ Panduit Color Code	Red
▪ Plating Type	Tinned
▪ Pricing Description	Terminal Convenience Package
▪ Stock	0.03
▪ Stock (mm)	0.8
▪ Stud Size	#6
▪ Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
▪ Tool	CT-100A‡, CT -600-A‡, CT -1550‡, CT-1551‡, CT-2500‡
▪ Wire Range	22 – 18 AWG
▪ Wire Range (mm²)	1.0 – 2.5
▪ Min. Order UOM	PC
▪ Min. Order Qty.	20
▪ BOM Qty. (# of Pkgs.)	0
▪ Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.