

Catalog No. TY5242MX

Description: CBL TIE 30LB 8IN UV BLACK 2-PC DIST

UPC No 786210869889

Home > Wire & Cable Management > Ty-Rap > Cable ties

Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 208mm (8.2 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 178 Newtons (40 Pounds)



Representative Image

Descriptors

| | |
|------------------|--|
| Category | Cable ties |
| Type | High Performance |
| Special Features | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |

Specifications

| | |
|------------------|-------------------------|
| Material | Nylon/Polyamide 6.6 |
| Color | Black |
| Lock Mechanism | Stainless Steel Barb |
| Tensile Strength | 40 pounds , 178 newtons |

Classifications

| | |
|------------|--------|
| Brand Name | Ty-Rap |
|------------|--------|

Dimensions

| | |
|-----------------|------------------------------|
| Width | 0.14 in , 3.6 mm |
| Length | 8.2 in , 208 mm |
| Thickness | 0.04 in , 1.0 mm |
| Bundle Diameter | 0.08 to 2.01 in , 2 to 51 mm |

Compliance and Certifications

| | |
|------|-----------------------------|
| RoHS | RoHS3 Compliant |
| TSCA | TSCA Section 6(h) Compliant |

ETIM Classification

| | |
|------------|--------------------|
| ETIM | EC000046 Cable tie |
| Band width | 3.6 mm |

| | |
|--------------------------|--------------------|
| ETIM | EC000046 Cable tie |
| Length belt/tape/tie | 208 mm |
| Length belt/tape/tie | 8.2 inch |
| Tie thickness | 1 mm |
| Tie thickness | 0.04 inch |
| Max. bundle diameter | 51 mm |
| Min. holding force | 178 N |
| Operation temperature | -40-+85 °C |
| Operation temperature | -40-+185 °F |
| Model | Internal toothing |
| Band closure | Steel nose |
| Material | Plastic |
| Material quality | Polyamide (PA) |
| Surface protection | Untreated |
| Halogen free | Y |
| Colour | Black |
| Transparent | N |
| Reflective (fluorescent) | N |
| Text strip | None |
| Solvable fastener | N |
| MIL approval | N |
| UL approval | Y |