



Part Number : [5054311000](#)

Product Description : Micro-Lock Plus Female Crimp Terminal, Tin (Sn) Plating, 30-26 AWG, Reel

Series Number : 505431

Status : Active

Product Category : Crimp Terminals



Documents & Resources

Drawings

[Drawing 5054311000_sd.pdf](#)

3D Models and Design Files

[3D Model 5054311000_stp.zip](#)

Specifications

[Application Specification 5054320000-AS-000.pdf](#)

[Application Specification 5055650000-AS-000.pdf](#)

[Packaging Specification 5054319200-200.pdf](#)

[Product Specification 2045230000-PS-000.pdf](#)

[Product Specification 2045230001-PS-000.pdf](#)

[Product Specification 2045231001-PS-000.pdf](#)

[Product Specification 2045320000-PS-000.pdf](#)

[Product Specification 2045320001-PS-000.pdf](#)

[Product Specification 2045320002-PS-000.pdf](#)

[Product Specification 2045321001-PS-000.pdf](#)

[Product Specification 2145260000-PS-000.pdf](#)

[Product Specification 2145260001-PS-000.pdf](#)

[Product Specification 2145260002-PS-000.pdf](#)

[Product Specification 2145260003-PS-000.pdf](#)

[Product Specification 2145270000-PS-000.pdf](#)

[Product Specification 2145270001-PS-000.pdf](#)

[Product Specification 5054320000-002.pdf](#)

[Product Specification 5054320000-005.pdf](#)

[Product Specification 5054321000-PS-002.pdf](#)

[Product Specification 5055650000-000.pdf](#)

[Product Specification 5055650003-PS-000.pdf](#)

[Product Specification 5055651000-PS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 34
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Crimp Terminals
Series	505431
Description	Micro-Lock Plus Female Crimp Terminal, Tin (Sn) Plating, 30-26 AWG, Reel
Application	Signal, Wire-to-Board
Product Family	Micro-Lock Connector System
Product Name	Micro-Lock Plus
UPC	889056302913

Electrical

Current - Maximum per Contact	1.5A
Voltage - Maximum	50V AC (RMS)/DC

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	16.620/mg
Packaging Type	Reel
Plating min - Mating	0.700µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	0.78-1.02mm
Wire Size (AWG)	26, 28, 30
Wire Size mm ²	0.049-0.136

Use with Part(s)

Description	Part Number
1.25mm Pitch, Micro-Lock Plus Dual Row Receptacle Housings	<u>505432</u>
1.25mm Pitch, Micro-Lock Plus Single Row Receptacle Housings	<u>505565</u>

Application Tooling

Global

Description	Part Number
Hand Crimp Tool for Micro-Lock Plus 1.25mm Pitch Wire-to-Board Receptacle Terminals, 30-26 AWG, UL1061 wire	<u>2002180300</u>
Extraction and Activation Tool	<u>638132700</u>
FineAdjust Applicator for Micro-Lock Plus, 1.25mm (.049") Wire to Board Crimp Terminal, 30-26 AWG	<u>639042300</u>

Application Tooling

Japan

Description	Part Number
-------------	-------------

S-1 Applicator for Micro-Lock Plus Terminals, 30-26 AWG	<u>5781463700</u>
--	-------------------

This document was generated on Sep 19, 2024