


G fuse link DIN 41662 slow-response Low breaking capacity Rated continuous current 1 A



Model		
product brand name	SETRON	
product designation	G fuse link	
design of the product	time-lag (T)	
type of miniature fuse	glass fuse	
General technical data		
size of the fuse link	5 x 20 mm	
melting characteristics	slow acting (T)	
type of voltage of the operating voltage	AC	
operating voltage rated value	250 V	
Main circuit		
operational current rated value	1 A	
Display and operation		
product component visual defect indication	No	
Mechanical Design		
net weight	1 g	
Approvals Certificates		
General Product Approval	other	Environment

[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

[Environmental Con-
firmations](#)

Environment

[Environmental Con-
firmations](#)

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1822-7EF76
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/8WA1822-7EF76
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1822-7EF76

last modified: 1/14/2024 

