



RECOMMENDED PCB LAYOUT

规格说明:Specifications:
电气特性:Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
300 V AC For one minuter
5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

原材料:Raw material:

1. 塑胶:Plastic cement:
Hing Temperature Thermoplastics,
LCP Black/Nature
 2. 端子:Contact:Copper Alloy C5191/C2680
 3. 外壳:Shell: Copper Alloy C2680
- 电镀:Electroplate:
1. 端子:Contact: Plated Gold in Mating Area;
Tin On Solder Tails
 2. 外壳:Shell:
Nickel Plating

 深圳市万骏达电子有限公司 http://www.wanjunda.com		页码 (SHEET)		单位 (UNIT): MM
品名 (ITEM NO)	MINI USB 5P/F180° DIP B型	版本 (REV)		比例 (SCALE) 1:1
料号 (PART NO)	MINI-5F-ZCS-01	日期 (DATE)		 未注公差 TOLERANCE UNSPECIFIED X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X° ±5° X.X° ±2°
图号 (DWG NO)		设计 (DESIGN)		
		审核 (CHECKED)		
		核准 (APPROVED)		