


Ordering Information:
 A1501WV-XP - ** - *** - ***
 1 2 3 4

- Part NO.
- Material:
 (Blank):Nylon 66,UL94V-0
 GWT: Nylon 66,UL94V-0,
 IEC 60335-1,5th Edition
 Glow Wire Capable.
- Color:
 (Blank):Ivory
 BK:Black
 BL:Blue
 RD:Red
 GN:Green
 GY:Gray
 YL:Yellow
- Finish:
 (Blank):Tin over Nickel
 G:Gold over Nickel



SPECIFICATIONS:
 Current Rating: 2A AC,DC (AWG #24)
 Voltage Rating: 100V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	1.50	4.50	8P	10.50	13.50
3P	3.00	6.00	9P	12.00	15.00
4P	4.50	7.50	10P	13.50	16.50
5P	6.00	9.00	11P	15.00	18.00
6P	7.50	10.50	12P	16.50	19.50
7P	9.00	12.00	13P	18.00	21.00

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE
mm	5:1	1 of 1	
DRAWN	CHK'D	APPR	
Chengbiao Ye	Diankui Wan	Jack Yin	1.50mm Pitch Vertical Wafer
DRAWING NO.			
A1501WV-XP			REV A0

A0	NEW RELEASE	2005.05.10
REV	DESCRIPTION	DATE

General Tolerances
 x.xx±0.25
 x.xxx±0.20
 x.xxxx±0.15
 ANGLES ±1°

THIRD ANGLE PROJECTION